




モータ保護専用		モータ保護兼用					
3P, 3E, 30 A	2P, 2E, 50 A	2P, 2E, 50 A	3P, 3E, 50 A	2P, 2E, 100 A	3P, 3E, 100 A	2P, 2E, 125 A	3P, 3E, 125 A
3φ3W	1φ2W	1φ2W	(1φ3W), 3φ3W	1φ2W	(1φ3W), 3φ3W	1φ2W	(1φ3W), 3φ3W
220	220	460		460		460	
	100	125		250		250	
0.2KW(1.3A), 0.4(2.6), 0.75(4.2) 1.0(5.5), 1.5(7.4), 2.2(10), 3.7(16) 5.5(25), 7.5(32)	40, 50	● 15, 20, 30 ● 35, 40, 50		50, 60, 75, 100		125	
M-3 B	B-52 C	B-52	B-53	B-102	B-103	B-122 C	B-123 C
36	37	38, 39		40, 41		42, 43	
新製品 							
盤内仕様P36参照							
	5,000	5,000		10,000		10,000 / 10,000	
2,500	2,500	2,500		7,500		7,500 / 7,500	
		1,500		5,000		5,000 / 5,000	
	700(100V)	700		7,500		7,500	
				5,000		5,000	
105	45	75		90		90	
155	117	115(130端子カバー付)		141(161端子カバー付)		141(161端子カバー付)	
60.8	46	63		68		68	
77.2	63.5	82		90		90	
40	40	40		40		40	
線押え方式	線押え方式	線押え方式		標準品 圧着端子方式・受注品 溶ダレス端子方式		標準品 圧着端子方式・受注品 溶ダレス端子方式	
○	○	○		○		○	
		○		○		○	
		○		○		○	
○		○		○		○	
○		○		○		○	
		○		○		○	
		○		○		○	
		○		○		○	
		○		○		○	
14	22	22		50		50	
完全電磁	熱動電磁	熱動電磁		熱動電磁		熱動電磁	
▽取得済	▽取得済	▽取得済		▽取得済		▽対象外	
0.6	0.25	0.4	0.45	0.94	1.0	0.94	1.0
10	50	10		10		10	
3,400	3,100	3,500	4,000	9,200	10,200	14,400	15,400