





2P, 2E, 2000A		3P, 3E, 2000A		2P, 2E, 2500A		3P, 3E, 2500A		2P, 2E, 3200A		3P, 3E, 3200A		3P, 3E, 4000A		
1φ2W		3φ3W		1φ2W		3φ3W		1φ2W		3φ3W		3φ3W		
600		600		600		600		600		600		600		
●1, 800, ●2, 000		●2, 500		●3, 000, ●3, 200		●3, 600, ●4, 000								
B-2002 F		B-2003 F		B-2502 F		B-2503 F		B-3202 F		B-3203 F		B-4003 F		
80, 81		82, 83		84		85								
														
150, 000 / 125, 000		150, 000 / 125, 000		150, 000 / 125, 000		150, 000 / 125, 000								
100, 000 / 85, 000		100, 000 / 85, 000		100, 000 / 85, 000		100, 000 / 85, 000								
80, 000 / 70, 000		80, 000 / 70, 000		80, 000 / 70, 000		80, 000 / 70, 000								
310		310		530		750								
560 (760バー端子含む)		560		610		650								
226		226		304		374								
299 (403補助ハンドル付)		299 (403補助ハンドル付)		373 (590補助ハンドル付)		428.5 (698.5補助ハンドル付)								
40		40		40		40								
裏面バースタッド方式		裏面バースタッド方式		裏面バースタッド方式		裏面バースタッド方式								
○ (裏面形が標準本体●印) 表面形, 埋込形は▲印		○ (裏面形が標準本体●印) 埋込形は▲印		○ (裏面形が標準本体●印)		○ (裏面形が標準本体●印)								
○		○												
○		○		○		○								
○		○		○		○								
○		○		○		○								
○		○		○		○								
○		○		○		○								
○		○		○		○								
熱動可調整電磁		熱動可調整電磁		熱動電磁		熱動電磁								
▽対象外		▽対象外		▽対象外		▽対象外								
70		84		200		250								
1		1		1		1								
655,000	696,000	837,000	867,000	1,395,000	1,457,000	2,360,000								