

Technical drawings of the K2000 Series Locking Cabinet, showing front, side, and top views with dimensions and labels for mounting and locking options.

Front View (Left): Shows the cabinet with dimensions 325 (height), 365 (height to top edge), 485 (width), and 455 (width to right edge). The door thickness is 25 mm.

Side View (Left): Shows the cabinet with dimensions 325 (height), 107 (height to top edge), 78 (height to bottom edge), and 100 (height to base).

Top View (Left): Shows the cabinet with dimensions 455 (width), 37 (width to center), 37 (width to center), 37 (width to center), 37 (width to center), 45 (width to center), 53 (width to center), 53 (width to center), 50 (width to center), 80 (width to center), and 100 (width to center).

Front View (Right): Shows the cabinet with dimensions 325 (height), 365 (height to top edge), 485 (width), and 455 (width to right edge). The door thickness is 25 mm.

Side View (Right): Shows the cabinet with dimensions 325 (height), 107 (height to top edge), 78 (height to bottom edge), and 100 (height to base).

Top View (Right): Shows the cabinet with dimensions 455 (width), 37 (width to center), 37 (width to center), 37 (width to center), 37 (width to center), 45 (width to center), 53 (width to center), 53 (width to center), 50 (width to center), 80 (width to center), and 100 (width to center).

Labels:

- 埋込形 (Built-in type)
- 露出形 (Exposed type)
- 2- ϕ 28 W/ノックアウト (2- ϕ 28 W/No knock out)
- 2- ϕ 28 W/ノックアウト (2- ϕ 28 W/No knock out)
- 6- ϕ 5 板枠用サイドノック (6- ϕ 5 Plate frame side lock)

3-配線用ソックアウト37×19

塗代カバー取付穴

配線穴

配線カバー

55

52

15

144

160

280

46

46

46

48

58

72

83.5

246

128