

[illegible]

3SPN

6-配線用ロックアウト37×19

塗代カバー取付穴

6-φ5取付穴

600V IV電線14φ

配線穴

配線カバー

木台 220×90

Dimensions: 55, 55, 80, 55, 55, 100, 82, 68, 51, 33, 100, 310, 220, 530, 171, 220, 128, 63, 33, 76, 65, 35, 74, 83.5, 46, 46, 46, 46, 46, 46, 30, 83.5, 270, 135, 490, 220, 90.

[illegible]

Technical drawings of the K2000 series lock system, showing front, side, and top views for both '埋込形' (Flush Mount) and '露出形' (Exposed Mount) configurations. Dimensions are provided in millimeters.

埋込形 (Flush Mount):

- Overall width: 525mm
- Overall height: 107mm
- Lock body dimensions: 10-φ28Wノックアウト, 2-φ34Wノックアウト
- Internal dimensions: 51-45-37-37-37-37-37-37-45-51
- Side view dimensions: 325mm (height), 355mm (depth), 555mm (width), 525mm (width), 25mm (thickness)
- Bottom view dimensions: 250mm (width), 25mm (thickness)
- 6-φ5板枠用サイドノック (6-φ5 plate frame side lock)

露出形 (Exposed Mount):

- Overall width: 496mm
- Overall height: 100mm
- Lock body dimensions: 10-φ28Wノックアウト, 2-φ34Wノックアウト
- Internal dimensions: 37-37-37-62-37-74-37-37-37-37-37
- Side view dimensions: 325mm (height), 355mm (depth), 555mm (width), 525mm (width), 25mm (thickness)
- Bottom view dimensions: 218.5mm (width), 437mm (width), 240mm (height), 220mm (height)