






配線用しゃ断器 (2P)

汎用シリーズ

受注 区分	品 名	極数・素子・ 容量			標準価格 (円)	電圧(V)	フレーム	定格しゃ断電流	一梱 入数		寸法図 番 号
○	B-52C	2P2E 40A			3,780	220 (DC=100V)	50AF	AC 110V 5,000A AC 220V 2,500A DC 100V 700A	50		P23 4
○		2P2E 50A									
●	B-52N	2P2E 15A			4,130	460 (DC=125V)	50AF	AC 110V 5,000A AC 220V 2,500A AC 460V 1,500A DC 125V 700A	10		P25 11
○		2P2E 20A									
○		2P2E 30A									
○		2P2E 40A									
○		2P2E 50A									
○	B-102N	2P2E 50A			12,400	460 (DC=250V)	100AF	AC 110V 10,000A AC 220V 7,500A AC 460V 5,000A DC 125V 7,500A DC 250V 5,000A	10		P25 12
○		2P2E 60A									
○		2P2E 75A									
○		2P2E 100A									
○	B-122C	2P2E 125A			20,300	460 (DC=250V)	125AF	AC 110V 10,000/10,000A AC 220V 7,500/7,500A AC 460V 5,000/5,000A DC 125V 7,500A DC 250V 5,000A	10		P25 12
○		2P2E 150A									
●	B-222C	2P2E 125A			28,500	460 (DC=250V)	225AF	AC 110V 23,000/22,000A AC 220V 16,000/15,000A AC 460V 10,000/10,000A DC 125V 15,000A DC 250V 10,000A	5		P26 13
○		2P2E 150A									
○		2P2E 175A									
○		2P2E 200A									
○		2P2E 225A									
●	B-252	2P2E 150A			37,600	460 (DC=250V)	250AF	AC 110V 35,000/30,000A AC 220V 35,000/30,000A AC 460V 16,000/15,000 DC 125V 25,000A DC 250V 20,000A	1		P26 14
●		2P2E 175A									
●		2P2E 200A									
●		2P2E 225A									
○		2P2E 250A									
●	B-402C	2P2E 250A			54,600	460 (DC=250V)	400AF	AC 110V 35,000/30,000A AC 220V 35,000/30,000A AC 460V 16,000/15,000A DC 125V 25,000A DC 250V 20,000A	1		P27 15
○		2P2E 300A									
○		2P2E 400A			69,700						
●	B-602H	2P2E 500A			195,500	600 (DC=250V)	600AF	AC 220V 50,000/42,000A AC 460V 25,000/22,000A AC 600V 20,000/18,000A DC 125V 40,000A DC 250V 40,000A	1		P27 16
●		2P2E 600A									