







漏電しゃ断器 (2P)




OC付 過負荷・短絡保護兼用

GBシリーズ

受注 区分	品 名	極数・素子・ 容 量			標準価格 (円)	感度電流 (mA)	電圧(V)	フレーム	定格しゃ断電流	一梱 入数		寸法図 番						
○	GB-Z	2P1E 20A			4,000	15 ・ 30	100	30AF	AC 110V 1,500A	50		P57 1						
○		2P1E 30A																
○	GB-1E	2P1E 15A			5,280	15 ・ 30	100	30AF	AC 110V 1,500A	20		P57 2						
○		2P1E 20A																
○		2P1E 30A																
○	GB-2C	2P2E 15A			5,630	15 ・ 30	100-100/200	30AF	AC 110V 1,500A AC 110/220V 1,500A	20		P57 2						
○		2P2E 20A																
○		2P2E 30A																
●	GB-52S	2P2E 15A			10,200	30	100-200	50AF	AC 110V 5,000A AC 110/220V 5,000A AC 220V 2,500A	10		P63 24						
○		2P2E 20A																
○		2P2E 30A																
○		2P2E 50A																
●	GB-52	2P2E 15A			11,100	30	100-200	50AF	AC 110V 2,500A AC 220V 2,500A	10		P57 5						
●		2P2E 20A																
○		2P2E 30A																
○		2P2E 40A																
○		2P2E 50A																

注 ① ○標準品 ② ●受注品(納期2~3週間) ③ ●受注品(納期1~3ヶ月) ④ 100/200V表示は単相3線式回路での200V使用を示します。

GT-Z・GB-Z用埋込金具・プレート(別売品)

金具	1ヶ用プレート	取付例
		
標準価格 金具+1ヶ用プレート=¥440		