



裏面形漏電しゃ断器（4P）OC付 過負荷・短絡保護兼用

受注区分	品名	極数・素子・容量			標準価格 (円)	感度電流 (mA)	電圧(V)	フレーム	定格しゃ断電流	一相 入数
●	GB-54	4P3E 15A			71,400	30	415	50AF	AC415V 50/42KA	1
●		4P3E 20A								
●		4P3E 30A								
●		4P3E 50A								
●	GB-104	4P3E 60A			127,820	30	415	100AF	AC415V 50/42KA	1
●		4P3E 75A								
●		4P3E 100A								
●	GB-224	4P3E 125A			192,000	30	415	225AF	AC220V 100/85KA AC415V 30/25KA	1
●		4P3E 150A								
●		4P3E 200A								
●		4P3E 225A								
●	GB-404	4P3E 300A			370,000	30	415	400AF	AC220V 100/85KA AC415V 40/35KA	1
●		4P3E 400A								
●	GB-804	4P3E 800A			831,600	100/200/500 切替	415	800AF	AC220V 100/85KA AC415V 40/35KA	1
●	GB-1004	4P3E 1,000A			1,394,200	100/200/500 切替	415	1,000AF	AC220V 100/85KA AC415V 40/35KA	1

埋込形漏電しゃ断器（2P）OC付 過負荷・短絡保護兼用

●	GB-62H	2P2E 15A			17,040	30	100-200	60AF	AC110V 2,500A AC220V 2,500A	1	P58 7
●		2P2E 20A									
●		2P2E 30A									
●		2P2E 40A									
●		2P2E 50A									
●		2P2E 60A			17,560	15・30					
●	GB-72	2P2E 75A			22,780	15・30	100-200	75AF	AC110V 5,000A AC220V 5,000A	1	P58 7
●	GB-102	2P2E 50A			29,360	30	100-200	100AF	AC110V 10,000A AC220V 7,500A	1	P58 8
●		2P2E 60A									
●		2P2E 75A									
●		2P2E 100A									
●	GB-122C	2P2E 125A			30,200	30 50/100/200 切替	100-200	125AF	AC110V 10,000/10,000A AC220V 7,500/7,500A	1	P58 8
●	GB-222C	2P2E 150A			51,040	30 50/100/200 切替	100 ・ 200	225AF	AC110V 23,000/20,000A AC220V 16,000/15,000A	1	P59 9
●		2P2E 175A									
●		2P2E 200A									
●		2P2E 225A									

埋込形漏電しゃ断器（3P）OC付 過負荷・短絡保護兼用

●	GB-63H	3P3E 15A			18,340	30	(100/200) 200 ・ ●415	60AF	AC220V 2,500A AC415V 2,500A	1	P58 7
●		3P3E 20A									
●		3P3E 30A									
●		3P3E 40A									
●		3P3E 50A									
●		3P3E 60A			19,120	15・30 100					
●	GB-73	3P3E 75A			24,500	15・30 100	(100/200) 200 ・ ●415	75AF	AC220V 5,000A AC415V 2,500A	1	P58 7

注 ① ○標準品 ② ●受注品(納期2～3週間) ③ ●受注品(納期1～3ヶ月) ④ 定格しゃ断電流<非対称/対称> ⑤ 100/200V表示は単相3線式回路での200V使用を示します。