



	モータ保護兼用		モータ保護専用	
2P, 2E, 30A	3P, 3E, 30A	3P, 3E, 30A	2P, 2E, 50A	3P, 3E, 30A
1φ2W	(1φ3W), 3φ3W	3φ3W	1φ2W	(1φ3W), 3φ3W
250	220	220	220	460
100			100	
10, 15, 20, 30	1.3(0.2kw相当), 2.6(0.4), 4.2(0.75), 5.5(1.0), 7.4(1.5), 10(2.2), 15(3.7), 20, 25(5.5), 30(7.5)	0.2KW(1.3A), 0.4(2.6), 0.75(4.2), 1.0(5.5), 1.5(7.4), 2.2(10), 3.7(16), 5.5(25), 7.5(32)	15, 20, 30, 40, 50	15, 20, 30
JB-32H	B-33M	M-3B	B-52C	B-33E
30	31	32	33	34, 35
				
NK認定・ロイド登録		盤内仕様P 32参照		
5,000(125V)			5,000	
2,500(250V)	2,500(220V)	2,500(220V)	2,500(220V)	2,500(220V)
				1,500
700(100V)			700(100V)	
45	70	105	45	70
117	105(115端子カバー付)	155	117(121端子カバー付)	105(115端子カバー付)
46	49	60.8	46	49
63.5	72.2	77.2	63.5	69
45	40	40	40	40
線押え方式 (圧着端子使用可能)	線押え方式 (圧着端子使用可能)	線押え方式 (圧着端子使用可能)	線押え方式 (圧着端子使用可能)	線押え方式 (圧着端子使用可能)
○	○	○(別売)	○	○
				○
				○
	○	○		○
	○	○		○
				○
	○			○
22	14	14	22	22
熱動電磁	完全電磁	完全電磁	熱動電磁	熱動電磁
▽取得済	▽取得済	▽取得済	▽取得済	▽取得済
0.25	0.42	0.6	0.25	0.4
50	10	10	50	20
2,560	3,780	4,130	3,780	3,600