




2P, 2E, 2500 A		3P, 3E, 2500 A		2P, 2E, 3200 A	3P, 3E, 3200 A	3 P, 3 E, 4000 A			
1φ2W		3φ3W		1φ2W	3φ3W	3φ3W			
600		600		600					
●2,500		●3,000, ●3,200		●3,600, ●4,000					
B-2502 F	B-2503 F	B-3202 F	B-3203 F	B-4003 F					
76, 77		78		79					
									
150,000 / 125,000		150,000 / 125,000		150,000 / 125,000					
100,000 / 85,000		100,000 / 85,000		100,000 / 85,000					
80,000 / 70,000		80,000 / 70,000		80,000 / 70,000					
310		530		750					
560		610		650					
226		304		374					
299 (403補助ハンドル付)		373 (590補助ハンドル付)		428.5 (698.5補助ハンドル付)					
40		40		40					
裏面バースタッド方式		裏面バースタッド方式		裏面バースタッド方式					
○		○		○					
○									
○		○		○					
○		○		○					
○		○		○					
○		○		○					
○		○		○					
○		○		○					
熱動可調整電磁		熱動電磁		熱動電磁					
▽対象外		▽対象外		▽対象外					
84		200		250					
1		1		1					
1,378,000	1,531,000	2,338,000	2,597,000	3,553,000					
(裏面形が標準本体) (納期●印)		(裏面形が標準本体) (納期●印)		(裏面形が標準本体) (納期●印)					