



4P, 3E, 1000 A	4P, 3E, 1600 A	4P, 3E, 2000 A		
3φ4W	3φ4W	3φ4W		
600	600	600		
●1,000	●1,000, ●1,200 ●1,400, ●1,600	●1,800, ●2,000		
B-1004F	B-1604F	B-2004F		
90, 91	92, 93	94		
				
100,000 / 85,000	150,000 / 125,000	150,000 / 125,000		
40,000 / 35,000	100,000 / 85,000	100,000 / 85,000		
20,000 / 18,000	80,000 / 70,000	80,000 / 70,000		
280	415	415		
410 (570バー端子含む)	560 (760バー端子含む)	560 (760バー端子含む)		
126	226	226		
188	299 (403補助ハンドル付)	299 (403補助ハンドル付)		
40	40	40		
バー端子方式	裏面バースタッド方式	裏面バースタッド方式		
○	○	○		
○	○	○		
○	○	○		
○	○	○		
○	○	○		
○	○	○		
○	○	○		
○	○	○		
熱動可調整電磁	熱動可調整電磁	熱動可調整電磁		
▽対象外	▽対象外	▽対象外		
33	85	87		
1	1	1		
1,120,000	1,697,000 (裏面形が標準本体(納期●印)) (表面形は別途ご相談ください)	1,960,000 (裏面形が標準本体(納期●印)) (表面形は別途ご相談ください)		