

テナント用(WHMスペース付)/マンセル5Y7/1



TWG1012



主幹：漏電しゃ断器〈单相3線式〉

分岐：安全ブレーカ2P20A・100V配線

主 幹	型 式	分 岐 回路数	予 備 回路数		標準価格 (円)	寸 法 (mm)			適 用 ボックス	外 形 寸法図 No.
						タ	テ	ヨ	コ	フカサ
3P 50A	● TWG506-6	6 ⁴	6		72,200	1,150	400	180	I	191
	● TWG508-4	8 ⁴	4		75,700	1,150	400	180	I	191
	● TWG510-2	10 ⁴	2		79,300	1,150	400	180	I	191
	● TWG512	12 ⁴	0		82,000	1,150	400	180	I	191
	● TWG514-4	14 ⁶	4		85,500	1,250	400	180	H	190
	● TWG516-2	16 ⁶	2		89,000	1,250	400	180	H	190
	● TWG518	18 ⁶	0		93,400	1,250	400	180	H	190
3P 60A	● TWG606-6	6 ⁴	6		72,200	1,150	400	180	I	191
	● TWG608-4	8 ⁴	4		75,700	1,150	400	180	I	191
	● TWG610-2	10 ⁴	2		79,300	1,150	400	180	I	191
	● TWG612	12 ⁴	0		82,000	1,150	400	180	I	191
	● TWG614-4	14 ⁶	4		85,500	1,250	400	180	H	190
	● TWG616-2	16 ⁶	2		89,000	1,250	400	180	H	190
	● TWG618	18 ⁶	0		93,400	1,250	400	180	H	190
3P 75A	● TWG710-2	10 ⁴	2		89,000	1,150	400	180	I	191
	● TWG712	12 ⁴	0		93,400	1,150	400	180	I	191
	● TWG714-4	14 ⁶	4		96,900	1,250	400	180	H	190
	● TWG716-2	16 ⁶	2		100,400	1,250	400	180	H	190
	● TWG718	18 ⁶	0		103,800	1,250	400	180	H	190
	● TWG720-4	20 ⁸	4		107,400	1,350	400	180	G	189
	● TWG722-2	22 ⁸	2		110,900	1,350	400	180	G	189
	● TWG724	24 ⁸	0		114,500	1,350	400	180	G	189
3P 100A	TWG1010-2	10 ⁴	2		89,000	1,150	400	180	I	191
	TWG1012	12 ⁴	0		93,400	1,150	400	180	I	191
	TWG1014-4	14 ⁶	4		96,900	1,250	400	180	H	190
	TWG1016-2	16 ⁶	2		100,400	1,250	400	180	H	190
	TWG1018	18 ⁶	0		103,800	1,250	400	180	H	190
	TWG1020-4	20 ⁸	4		107,400	1,350	400	180	G	189
	TWG1022-2	22 ⁸	2		110,900	1,350	400	180	G	189
	TWG1024	24 ⁸	0		114,500	1,350	400	180	G	189

注) ①●印受注品 ②分岐回路数の枠内の小さな数字は2P2Eの安全ブレーカー組込数を表わします。

③埋込形寸法はタテ40mm、ヨコ40mmを加えて下さい。 ④露出・埋込は同価格です。