


テナント用(WHMスペース付)/マンセル5Y7/1



TWB1012



主幹：配線用しゃ断器〈单相3線式〉

分岐：安全ブレーカ2P20A・100V配線

標準電灯分電盤

主 幹	型 式	分 岐 回路数	予 備 回路数		標準価格 (円)	寸 法 (mm)			適 用 ボックス	外 形 寸法図 No.
						タ テ	ヨ コ	フカサ		
3P 50A	● TWB506-6	6 ^④	6		59,500	1,150	400	180	I	191
	● TWB508-4	8 ^④	4		63,000	1,150	400	180	I	191
	● TWB510-2	10 ^④	2		66,500	1,150	400	180	I	191
	● TWB512	12 ^④	0		70,400	1,150	400	180	I	191
	● TWB514-4	14 ^⑥	4		74,000	1,250	400	180	H	190
	● TWB516-2	16 ^⑥	2		77,000	1,250	400	180	H	190
	● TWB518	18 ^⑥	0		80,500	1,250	400	180	H	190
3P 60A	● TWB606-6	6 ^④	6		59,500	1,150	400	180	I	191
	● TWB608-4	8 ^④	4		63,000	1,150	400	180	I	191
	● TWB610-2	10 ^④	2		66,500	1,150	400	180	I	191
	● TWB612	12 ^④	0		70,400	1,150	400	180	I	191
	● TWB614-4	14 ^⑥	4		74,000	1,250	400	180	H	190
	● TWB616-2	16 ^⑥	2		77,000	1,250	400	180	H	190
	● TWB618	18 ^⑥	0		80,500	1,250	400	180	H	190
3P 75A	● TWB710-2	10 ^④	2		77,000	1,150	400	180	I	191
	● TWB712	12 ^④	0		80,500	1,150	400	180	I	191
	● TWB714-4	14 ^⑥	4		84,000	1,250	400	180	H	190
	● TWB716-2	16 ^⑥	2		88,100	1,250	400	180	H	190
	● TWB718	18 ^⑥	0		91,600	1,250	400	180	H	190
	● TWB720-4	20 ^⑧	4		95,100	1,350	400	180	G	189
	● TWB722-2	22 ^⑧	2		98,700	1,350	400	180	G	189
	● TWB724	24 ^⑧	0		102,000	1,350	400	180	G	189
3P 100A	TWB1010-2	10 ^④	2		77,000	1,150	400	180	I	191
	TWB1012	12 ^④	0		80,500	1,150	400	180	I	191
	TWB1014-4	14 ^⑥	4		84,000	1,250	400	180	H	190
	TWB1016-2	16 ^⑥	2		88,100	1,250	400	180	H	190
	TWB1018	18 ^⑥	0		91,600	1,250	400	180	H	190
	TWB1020-4	20 ^⑧	4		95,100	1,350	400	180	G	189
	TWB1022-2	22 ^⑧	2		98,700	1,350	400	180	G	189
	TWB1024	24 ^⑧	0		102,000	1,350	400	180	G	189

注) ①●印受注品 ②分岐回路数の枠内の小さな数字は2P2Eの安全ブレーカー組込数を表わす。

③埋込形寸法はタテ40mm、ヨコ40mmを加えて下さい。 ④露出・埋込は同価格です。