



動力回路スペース付/マンセル5Y7/1



TMB1012



主幹：配線用しや断器〈单相3線式〉

分岐：安全ブレーカ2P20A・100V配線

標準電灯分電盤

主 幹	型 式	分 岐 回路数	予 備 回路数		標準価格 (円)	寸 法 (mm)			適 用 ボックス	外 形 寸法図 No.
						タ テ	ヨ コ	フカサ		
3P 50A	● TMB506-6	6 ⁴	6		65,100	800	780	180	L	194
	● TMB508-4	8 ⁴	4		68,700	800	780	180	L	194
	● TMB510-2	10 ⁴	2		72,200	800	780	180	L	194
	● TMB512	12 ⁴	0		75,700	800	780	180	L	194
	● TMB514-4	14 ⁶	4		79,300	900	780	180	K	193
	● TMB516-2	16 ⁶	2		82,000	900	780	180	K	193
	● TMB518	18 ⁶	0		85,500	900	780	180	K	193
3P 60A	● TMB606-6	6 ⁴	6		65,100	800	780	180	L	194
	● TMB608-4	8 ⁴	4		68,700	800	780	180	L	194
	● TMB610-2	10 ⁴	2		72,200	800	780	180	L	194
	● TMB612	12 ⁴	0		75,700	800	780	180	L	194
	● TMB614-4	14 ⁶	4		79,300	900	780	180	K	193
	● TMB616-2	16 ⁶	2		82,000	900	780	180	K	193
	● TMB618	18 ⁶	0		85,500	900	780	180	K	193
3P 75A	● TMB710-2	10 ⁴	2		84,000	800	780	180	L	194
	● TMB712	12 ⁴	0		88,100	800	780	180	L	194
	● TMB714-4	14 ⁶	4		91,600	900	780	180	K	193
	● TMB716-2	16 ⁶	2		95,100	900	780	180	K	193
	● TMB718	18 ⁶	0		98,700	900	780	180	K	193
	● TMB720-4	20 ⁸	4		102,000	1,000	780	180	J	192
	● TMB722-2	22 ⁸	2		105,000	1,000	780	180	J	192
	● TMB724	24 ⁸	0		109,000	1,000	780	180	J	192
3P 100A	TMB1010-2	10 ⁴	2		84,000	800	780	180	L	194
	TMB1012	12 ⁴	0		88,100	800	780	180	L	194
	TMB1014-4	14 ⁶	4		91,600	900	780	180	K	193
	TMB1016-2	16 ⁶	2		95,100	900	780	180	K	193
	TMB1018	18 ⁶	0		98,700	900	780	180	K	193
	TMB1020-4	20 ⁸	4		102,000	1,000	780	180	J	192
	TMB1022-2	22 ⁸	2		105,000	1,000	780	180	J	192
	TMB1024	24 ⁸	0		109,000	1,000	780	180	J	192

注) ①●印受注品 ②分岐回路数の枠内の小さな数字は2P2Eの安全ブレーカー組込数を表わします。

③埋込寸法はタテ40mm、ヨコ40mmを加えて下さい。 ④露出・埋込は同価格です。