

3 P

仕 様 型 式	動 作 時 間	高 速 形 (0.1秒以内)											
	電 圧	100-200V (GB-403C: 200-415V)						415V					
	感 度 電 流 (mA)	15	30	100	200	500	感 度 切 替	15	30	100	200	500	感 度 切 替
GB-123C	125A	●	○	●	●		○ 50/100/200	●	●	●	●		
GB-223S	125A		●	●	●	●	● 50/100/200		●	●	●	●	● 50/100/200
	150A		○	●	●	●	○ 50/100/200		●	●	●	●	● 50/100/200
	175A		○	●	●	●	○ 50/100/200		●	●	●	●	● 50/100/200
	200A		○	●	●	●	○ 50/100/200		●	●	●	●	● 50/100/200
	225A		○	●	●	●	○ 50/100/200		●	●	●	●	● 50/100/200
GB-253E	250A		○	●	●	●	○ 100/200/500		●	●	●	●	● 100/200/500
GB-403C	250A		●	●	●	●	● 100/200/500		●	●	●	●	● 100/200/500
	300A		○	●	●	●	○ 100/200/500		●	●	●	●	● 100/200/500
	400A		○	●	●	●	○ 100/200/500		●	●	●	●	● 100/200/500

仕 様 型 式	動 作 時 間	時 延 形 (0.3秒) 内 時間切替形											
	電 圧	100-200V						415V					
	感 度 電 流 (mA)	15	30	100	200	500	感 度 切 替	15	30	100	200	500	感 度 切 替
GB-123C	125A		●	●	●				●	●	●		
GB-223S	125A		●	●	●	●	● 50/100/200 0.1/0.3/0.5秒		●	●	●		● 50/100/200
	150A		●	●	●	●	● 50/100/200 0.1/0.3/0.5秒		●	●	●		● 50/100/200
	175A		●	●	●	●	● 50/100/200 0.1/0.3/0.5秒		●	●	●		● 50/100/200
	200A		●	●	●	●	● 50/100/200 0.1/0.3/0.5秒		●	●	●		● 50/100/200
	225A		●	●	●	●	● 50/100/200 0.1/0.3/0.5秒		●	●	●		● 50/100/200
GB-253E	250A		●	●	●	●	● 50/100/200 0.1/0.3/0.5秒		●	●	●		● 50/100/200
GB-403C	250A		●	●	●	●	● 100/200/500 0.1/0.3/0.5秒		●	●	●		● 50/100/200
	300A		●	●	●	●	● 100/200/500 0.1/0.3/0.5秒		●	●	●		● 50/100/200
	400A		●	●	●	●	● 100/200/500 0.1/0.3/0.5秒		●	●	●		● 50/100/200

注) ①表以外の器種については「仕様一覧表」を参照下さい。

② 0.1/0.3/0.5秒の時間切替形で0.1秒の設定は高速形(0.1秒以内動作)です。

仕様区分 ○標準品 ●準標準品 ●受注品