

2 P

仕 様 型 式	動 作 時 間	高 速 形 (0.1秒以内)										時 延 形 (0.3秒)										
	電 圧	100－200V					415V					100－200 V					415 V					
	感 電 度 電 流 (mA)	15	30	100	200	500	15	30	100	200	500	15	30	100	200	500	15	30	100	200	500	
GT-2Z GT-2E	30A	○	○																			
GB-1Z (100V) GB-2Z GB-2E	15A	○	○																			
	20A	○	○																			
	30A	○	○																			
GB-52E	15A	●	○				●	●	●	●												
	20A	●	○	●			●	●	●	●												
	30A	●	○	●			●	●	●	●												
	40A	●	○	●			●	●	●	●												
	50A	●	○	●			●	●	●	●												
GB-62E	60A	●	○	●			●	●	●	●												
GB-72E	75A	●	○	●	●		●	●	●	●			●	●				●	●	●		
GB-102E	50A		○				●	●	●	●								●	●	●		
	60A	●	○	●	●		●	●	●	●			●	●				●	●	●		
	75A	●	○	●	●		●	●	●	●			●	●				●	●	●		
	100A	●	○	●	●		●	●	●	●			●	●								
※ GB-122C	125A	●	●	●	●		●	●	●	●			●	●	●			●	●	●		
※ GB-222S	125A		●	●	●	●		●	●	●	●			●	●	●	●		●	●	●	
	150A		●	●	●	●		●	●	●	●			●	●	●	●		●	●	●	
	175A		●	●	●	●		●	●	●	●			●	●	●	●		●	●	●	
	200A		●	●	●	●		●	●	●	●			●	●	●	●		●	●	●	
	225A		●	●	●	●		●	●	●	●			●	●	●	●		●	●	●	

注) ※印:GB-122C, GB-222Sは感度切替形もあります。3 P の表を参照下さい。