

時延形●型式が一般のGBからGBLとなります。

動作時間**0.3**±50%

型式	電圧 感度電流 定格電流	200V (GBL-123C, 223S, 253Eは100-200V) (GBL-403Cは200-415V)						415V (GBL-403Cは200-415V)					
		15mA	30mA	100mA	200mA	500mA	感度切換形	15mA	30mA	100mA	200mA	500mA	感度切換形
GBL-73E	75A		●	●					●	●	●		
GBL-103E	50A			● 2Pは不可					●	●	●		
	60A		●	●					●	●	●		
	75A		●	●					●	●	●		
	100A		●	●									
GBL-123C	125A		●	●	●				●	●	●		
GBL-223S	150A		●	●	●	●	●50/100/200mA		●	●	●		●50/100/200mA
	175A		●	●	●	●	●50/100/200mA		●	●	●		●50/100/200mA
	200A		●	●	●	●	●50/100/200mA		●	●	●		●50/100/200mA
	225A		●	●	●	●	●50/100/200mA		●	●	●		●50/100/200mA
GBL-253E	250A		●	●	●	●	●50/100/200mA		●	●	●		●50/100/200mA
GBL-403C (200-415V)	300A		●	●	●		●50/100/200mA		●	●	●		●50/100/200mA
	400A		●	●	●		●50/100/200mA		●	●	●		●50/100/200mA

■一覧表に記載されていない器種については「仕様一覧表」をご参照下さい。

■GBL-123C～GBL-253Eの定格電圧は100-200Vです。

■GBL-223S, GBL-253Eは定格電圧200Vの場合0.1/0.3/0.5秒の時間切換形も製作可能です。(0.1秒の設定は0.1秒以内)

■GBL-123C, GBL-223S, GBL-253E, GBL-403Cは動作時間0.5秒又は、1.0秒の製作も可能です。

■2Pも上表に準じます。

仕様区分	○標準品	●標準品	●受注品
------	------	------	------