

VLG3

プラスチック製



















露出・半埋込兼用形

色：マンセル10Y8.5/1

ご注意

標準の漏電遮断器組込▶型式の末尾がJとなります。
単3中性線欠相保護付▶型式の末尾がHとなります。

単3 主幹：漏電遮断器

主幹	分岐回路数 + 予備回路数	仕様 区分	型式	標準価格(円)	一梱 入数	姿図 外形寸法(タテ×ヨコ×フカサ)mm	寸法図番号	回路図
3P・OC付 40A (30mA、高速形)	4+2	●	VLG3404-2(J) (H)	21,900	2		4	
	6+0	○	VLG3406(J) (H)	23,500	2			
	6+2	○	VLG3406-2(J) (H)	25,300	2		5	
	8+0	○	VLG3408(J) (H)	27,000	2			
	8+4	●	VLG3408-4(J) (H)	31,500	2		7	
	10+2	●	VLG3410-2(J) (H)	33,000	2			
	12+0	●	VLG3412(J) (H)	35,000	2		8	
	10+4	●	VLG3410-4(J) (H)	36,800	2			
	12+2	●	VLG3412-2(J) (H)	38,500	2		8	
	14+0	●	VLG3414(J) (H)	40,000	2			
3P・OC付 50A (30mA、高速形)	4+2	○	VLG3504-2(J) (H)	21,900	2		4	
	6+0	○	VLG3506(J) (H)	23,500	2			
	6+2	○	VLG3506-2(J) (H)	25,300	2		5	
	8+0	○	VLG3508(J) (H)	27,000	2			
	8+4	○	VLG3508-4(J) (H)	31,500	2		7	
	10+2	○	VLG3510-2(J) (H)	33,000	2			
	12+0	○	VLG3512(J) (H)	35,000	2		8	
	10+4	○	VLG3510-4(J) (H)	36,800	2			
	12+2	○	VLG3512-2(J) (H)	38,500	2		8	
	14+0	○	VLG3514(J) (H)	40,000	2			

●Hシリーズ型式末尾(H)
過電圧動作電圧125V±5V
過電圧動作時間0.5秒以内

●Hシリーズ型式末尾(H)
過電圧動作電圧125V±5V
過電圧動作時間0.5秒以内

住宅用分電盤

住宅用分電盤規格適合品認定マーク

仕様区分	○標準品	●準標準品	●受注品
------	------	-------	------

■200V用(2P2E)安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6~10	12~14
200V用(2P2E)実装数	0	1	2	4

■200V切替可能回路数(右端より)

総実装回路数	4	6	8	10	12	14
200V切替可能回路数	2	4	6	10		