

VG3

プラスチック製

















露出・半埋込兼用形

色：マンセル10Y8.5/1

ご注意

標準の漏電遮断器組込 ▶ 型式の末尾がJとなります。
 単3中性線欠相保護付 ▶ 型式の末尾がHとなります。

単3 主幹：漏電遮断器

主幹	分岐回路数 + 予備回路数	仕様 区分	型式	標準価格(円)	一捆 入数	姿図 外形寸法(タテ×ヨコ×フサ)mm	回路図
3P・OC付 30A (30mA、高速形)	3+1	○	VG3303-1 (J) (H)	13,000	10	 170×265×50 盤定格30A	
	4+0	○	VG3304 (J) (H)	13,900	10		
	4+2	○	VG3304-2S (J) (H)	16,900	4	 245×385×55 盤定格30A	
	6+0	○	VG3306S (J) (H)	18,700	4		
	4+2	○	VG3304-2 (J) (H)	16,900	5	 295×290×55 盤定格30A	
	6+0	○	VG3306 (J) (H)	18,700	5		
	6+2	○	VG3306-2 (J) (H)	19,700	5	 295×315×55 盤定格30A	
	8+0	○	VG3308 (J) (H)	21,500	5		
	8+4	●	VG3308-4 (J) (H)	24,700	2	 295×420×55 盤定格30A	
	10+2	●	VG3310-2 (J) (H)	26,500	2		
	12+0	●	VG3312 (J) (H)	28,200	2		
	6+0	○	VG3406S (J) (H)	21,600	4	 245×385×55 盤定格60A	
3P・OC付 40A (30mA、高速形)	4+2	○	VG3404-2 (J) (H)	19,800	5	 295×290×55 盤定格60A	
	6+0	○	VG3406 (J) (H)	21,600	5		
	6+2	○	VG3406-2 (J) (H)	23,100	5	 295×315×55 盤定格60A	
	8+0	○	VG3408 (J) (H)	24,900	5		
	8+4	●	VG3408-4 (J) (H)	27,000	2	 295×420×55 盤定格60A	
	10+2	●	VG3410-2 (J) (H)	29,000	2		
	12+0	●	VG3412 (J) (H)	30,500	2		

● Hシリーズ型式末尾(H)
 過電圧動作電圧125V±5V
 過電圧動作時間0.5秒以内

● Hシリーズ型式末尾(H)
 過電圧動作電圧125V±5V
 過電圧動作時間0.5秒以内

■ 200V用(2P2E)実全ブレーカ実装数(100V配線)

分岐回路数	3	4	6~10	12
200V用(2P2E)実装数	0	1	2	4

■ 200V切替可能回路数(右端より)

総実装回路数	4	6, 8	12
200V切替可能回路数	2	4	6

住宅用分電盤規格適合品認定マーク

仕様区分 ○ 標準品 ● 標準準品 ● 受注品