

VG3

プラスチック製

























露出・半埋込兼用形

色：マンセル10Y8.5/1

ご注意

標準の漏電遮断器組込▶型式の末尾が**J**となります。
 単3中性線欠相保護付▶型式の末尾が**H**となります。

単3 主幹：漏電遮断器

主幹	分岐回路数 + 予備回路数	仕様 区分	型式	標準価格(円)	一梱 入数	姿図 外形寸法(タテ×ヨコ×フカサ)mm 寸法図番号	回路図
3P・OC付 60A 〔30mA、高速形〕	6+0	●	VG3606 (J) (H)	21,600	5	 295×290×55 盤定格60A	 23
	6+2	●	VG3606-2 (J) (H)	23,100	5	 295×315×55 盤定格60A	 24
	8+0	●	VG3608 (J) (H)	24,900	5	 295×420×55 盤定格60A	 25
	8+4	○	VG3608-4 (J) (H)	27,000	2	 295×530×55 盤定格60A	 26
	10+2	○	VG3610-2 (J) (H)	29,000	2	 315×570×60 盤定格60A	 27
	12+0	○	VG3612 (J) (H)	30,500	2	 295×420×55 盤定格75A	 25
	12+4	○	VG3612-4 (J) (H)	33,000	2	 295×530×55 盤定格75A	 26
	14+2	○	VG3614-2 (J) (H)	34,800	2	 315×570×60 盤定格75A	 27
	16+0	○	VG3616 (J) (H)	36,600	2	 295×420×55 盤定格60A	 25
	14+4	○	VG3614-4 (J) (H)	35,900	2	 295×530×55 盤定格60A	 26
	16+2	○	VG3616-2 (J) (H)	37,600	2	 315×570×60 盤定格60A	 27
	18+0	○	VG3618 (J) (H)	39,400	2		
3P・OC付 75A 〔30mA、高速形〕	8+4	●	VG3708-4 (J) (H)	30,500	2	 295×420×55 盤定格75A	 25
	10+2	●	VG3710-2 (J) (H)	32,400	2	 295×530×55 盤定格75A	 26
	12+0	●	VG3712 (J) (H)	34,000	2	 315×570×60 盤定格75A	 27
	12+4	●	VG3712-4 (J) (H)	40,000	2		
	14+2	●	VG3714-2 (J) (H)	41,800	2		
	16+0	●	VG3716 (J) (H)	43,600	2		
	14+4	●	VG3714-4 (J) (H)	43,000	2		
	16+2	●	VG3716-2 (J) (H)	44,500	2		
	18+0	●	VG3718 (J) (H)	46,500	2		

●Hシリーズ型式末尾(H)
 過電圧動作電圧125V±5V
 過電圧動作時間0.5秒以内

●Hシリーズ型式末尾(H)
 過電圧動作電圧125V±5V
 過電圧動作時間0.5秒以内

■盤定格75Aは母線の最大容量です。

住宅用分電盤規格適合品認定マーク

仕様区分 ○標準品 ●標準品 ●受注品

■200V用(2P2E)安全ブレーカ実装数(100V配線)

分岐回路数	6～10	12～18
200V用(2P2E)実装数	2	4

■200V切替可能回路数(右端より)

総実装回路数	6, 8	12, 16	18
200V切替可能回路数	4	6	10