





















VB3

プラスチック製
露出・半埋込兼用形
色：マンセル10Y8.5/1

単3 主幹：配線用遮断器

主幹	分岐回路数 + 予備回路数	仕様 区分	型式	標準価格(円)	一 梱 入 数	姿図 外形寸法(タテ×ヨコ×フカサ)mm	寸法図番号	回路図
3P・3E 30A	4 +2	○	VB3304-2J	14,100	5		23	
	6 +0	○	VB3306J	15,900	5			
	6 +2	●	VB3306-2J	18,400	5		24	
	8 +0	●	VB3308J	20,000	5			
3P・3E 50A	6 +0	○	VB3506J	15,900	5		23	
	6 +2	○	VB3506-2J	18,400	5		24	
	8 +0	○	VB3508J	20,000	5			
	8 +4	○	VB3508-4J	21,000	2		25	
	10 +2	○	VB3510-2J	22,800	2			
	12 +0	○	VB3512J	24,700	2			
3P・3E 60A	6 +0	●	VB3606J	16,800	5		23	
	8 +0	●	VB3608J	21,000	5		24	
	8 +4	●	VB3608-4J	21,900	2		25	
	10 +2	●	VB3610-2J	23,700	2			
	12 +0	●	VB3612J	25,600	2			
3P・3E 75A	8 +0	●	VB3708J	27,800	5		24	
	8 +4	●	VB3708-4J	30,000	2		25	
	10 +2	●	VB3710-2J	31,800	2			
	12 +0	●	VB3712J	33,500	2			

■ 盤定格75Aは母線の最大容量です。

■ 200V用(2P2E)安全ブレーカ実装数(100V配線)

■ 200V切替可能回路数(右端より)

仕様区分 ○ 標準品 ● 準標準品 ● 受注品

分岐回路数	4	6 ~ 10	12
200V用(2P2E)実装数	1	2	4

総実装回路数	6, 8	12
200V切替可能回路数	4	6