

VG3-P

プラスチック製

露出・半埋込兼用形



















色：マンセル10Y8.5/I

フリースペース付 取付有効寸法
タテ220×ヨコ90mm

ご注意

標準の漏電遮断器組込 ▶ 型式の末尾が **J** となります。
単3 中性線欠相保護付 ▶ 型式の末尾が **H** となります。

単3 主幹：漏電遮断器

主幹	分岐回路数 + 予備回路数	仕様 区分	型式	標準価格(円)	一捆 入数	姿図 外形寸法(タテ×ヨコ×フカサ)mm	回路図
3P・OC付 30A 〔30mA、高速形〕 ●Hシリーズ型式末尾(H) 過電圧動作電圧125V±5V 過電圧動作時間0.5秒以内	4+2	○	VG3304-2P (J) (H)	21,200	2	 27	 27
	6+0	○	VG3306P (J) (H)	22,900	2		
	6+2	○	VG3306-2P (J) (H)	24,900	2	 29	 29
	8+0	○	VG3308P (J) (H)	26,600	2		
3P・OC付 40A 〔30mA、高速形〕 ●Hシリーズ型式末尾(H) 過電圧動作電圧125V±5V 過電圧動作時間0.5秒以内	4+2	○	VG3404-2P (J) (H)	24,100	2	 28	 28
	6+0	○	VG3406P (J) (H)	25,900	2		
	6+2	○	VG3406-2P (J) (H)	27,400	2	 29	 29
	8+0	○	VG3408P (J) (H)	29,100	2		
	10+2	○	VG3410-2P (J) (H)	33,600	2	 30	 30
	12+0	○	VG3412P (J) (H)	35,600	2		
3P・OC付 50A 〔30mA、高速形〕 ●Hシリーズ型式末尾(H) 過電圧動作電圧125V±5V 過電圧動作時間0.5秒以内	4+2	○	VG3504-2P (J) (H)	24,100	2	 28	 28
	6+0	○	VG3506P (J) (H)	25,900	2		
	6+2	○	VG3506-2P (J) (H)	27,400	2	 29	 29
	8+0	○	VG3508P (J) (H)	29,100	2		
	10+2	○	VG3510-2P (J) (H)	33,600	2	 30	 30
	12+0	○	VG3512P (J) (H)	35,600	2		
	12+2	○	VG3512-2P (J) (H)	38,500	2	 31	 31
	14+0	○	VG3514P (J) (H)	40,000	2		

住宅用分電盤規格適合品認定マーク

仕様区分 ○ 標準品 ● 準標準品 ● 受注品

■200V用(2P2E)安全ブレーカ実装数(100V配線)

分岐回路数	4	6~10	12~14
200V用(2P2E)実装数	1	2	4

■200V切替可能回路数(右端より)

総実装回路数	6, 8, 12	14
200V切替可能回路数	4	6