















**AB3
AC3**

扉付スチール製
露出形(S)/埋込形(F)
色：マンセル5Y8/2
ボックス板厚 1.2mm

単3 主幹：配線用遮断器

主幹	分岐回路数 + 予備回路数	仕様 区分	型式	標準価格(円)	一梱 入数	姿図 露出外形寸法(タテ×ヨコ×フカサ)mm	寸法図番号	回路図
3P・3E 30A	4+4	○	AB3304-4	露出 19,400 埋込 20,300	1		35	
3P・3E 50A	6+2	○	AB3506-2	露出 22,200 埋込 23,000	1		35	
	8+0	○	AB3508	露出 24,000 埋込 24,900	1			
	8+4	○	AB3508-4	露出 25,600 埋込 26,500	1		36	
	10+2	○	AB3510-2	露出 27,400 埋込 28,200	1			
3P・3E 100A	12+0	○	AB31012	露出 39,800 埋込 40,600	1		36	
	14+2	○	AB31014-2	露出 44,100 埋込 45,000	1			
	16+0	○	AB31016	露出 45,800 埋込 46,700	1		37	

単3 主幹：カバースイッチ(CKS)

主幹	分岐回路数 + 予備回路数	仕様 区分	型式	標準価格(円)	一梱 入数	姿図 露出外形寸法(タテ×ヨコ×フカサ)mm	寸法図番号	回路図
3P 30A	4+4	○	AC3304-4	露出 14,200 埋込 15,100	1		40	
3P 60A	6+2	○	AC3606-2	露出 17,400 埋込 18,300	1		40	
	8+0	○	AC3608	露出 19,000 埋込 19,900	1			
	8+4	○	AC3608-4	露出 21,600 埋込 22,500	1		41	
	10+2	○	AC3610-2	露出 23,200 埋込 24,100	1			

■200V用(2P2E)安全ブレーカ実装数(100V配線)

■200V切替可能回路数(右端より)

仕様区分 ○標準品 ●準標準品 ●受注品

分岐回路数	4	6~10	12~16
200V用(2P2E)実装数	1	2	4

総実装回路数	8	12	16
200V切替可能回路数	4	6	8