




















単3

主幹：単3中性線欠相保護付漏電遮断器

主幹	分岐回路数 +予備回路数	仕様 区分	型式	メーカー希望 小売価格 (円)	一 梱 入 数	姿図 外形寸法(タテ×ヨコ×フカサ)mm □寸法図番号(P.162~164)	回路図
3P OCなし 30A (30mA、高速形)	3+1	○	※VLG3303-1SH	12,850	4		
	4+0	○	※VLG3304SH	13,750	4		
	3+1	○	VLG3303-1H	12,850	5		
	4+0	○	VLG3304H	13,750	5		
	4+2	○	VLG3304-2H	14,100	5		
	6+0	○	VLG3306H	15,900	5		
	4+2	○	VLG3304-2MH	14,100	2		
	6+0	○	VLG3306MH	15,900	2		
3P OC付 30A (30mA、高速形)	6+2	○	VLG3306-2H	19,900	2		
	8+0	○	VLG3308H	21,600	2		
	4+4		VLG3304-4iH	17,400	4		
	6+2		VLG3306-2iH	19,200	4		
	8+0		VLG3308iH	21,000	4		
	8+2	○	VLG3308-2H	21,900	2		
	10+0	○	VLG3310H	23,500	2		
	6+4		VLG3306-4iH	22,900	2		
	8+2		VLG3308-2iH	24,700	2		
	10+0		VLG3310iH	26,500	2		
	8+4	○	VLG3308-4H	26,500	2		
	10+2	○	VLG3310-2H	28,300	2		
	12+0	○	VLG3312H	30,200	2		
	10+4	○	VLG3310-4H	33,500	2		
	12+2	○	VLG3312-2H	35,300	2		
	14+0	○	VLG3314H	36,900	2		

■※：リミッターの取付有効寸法は
タテ150×ヨコ90mmですのでご注意ください。

■200V用2P2E安全ブレーカ実装数(100V配線)

■200V切替可能回路数(右端より)

住宅用分電盤規格適合品認定マーク

分岐回路数	3	4	6~10	12~14
200V用(2P2E)実装数	0	1	2	4

総実装回路数	4	6, 8	10, 12	14	iシリーズ
200V切替可能回路数	2	4	6	10	全回路