
















単3

主幹: 単3 中性線欠相保護付漏電遮断器


主幹	分岐回路数 +予備回路数	仕様 区分	型式	露出 埋込	メーカー希望 小売価格 (円)	一極 入数	姿図 露出形外形寸法(タテ×ヨコ×フカサ)mm □ 寸法図番号(P.175)	回路図
3P OC付 30A (30mA、高速形)	3+1	○	KG3303-1H	露出 埋込	13,750	5	 199×289×54 盤定格30A 53	
	4+0	○	KG3304H	露出 埋込	14,650	5		
	4+2	○	KG3304-2H	露出 埋込	17,500	3	 279×304×60 盤定格30A 54	
	6+0	○	KG3306H	露出 埋込	19,300	3		
	6+2	○	KG3306-2H	露出 埋込	20,300	3	 279×339×60 盤定格30A 55	
3P OC付 40A (30mA、高速形)	6+0	○	KG3406H	露出 埋込	23,000	3	 279×304×60 盤定格40A 54	
	6+2	○	KG3406-2H	露出 埋込	24,000	3	 279×339×60 盤定格40A 55	
3P OC付 50A (30mA、高速形)	6+0	○	KG3506H	露出 埋込	23,000	3	 279×304×60 盤定格50A 54	
	6+2	○	KG3506-2H	露出 埋込	24,000	3	 279×339×60 盤定格50A 55	

●露出形



●埋込形

型式の末尾に-Fをつけて
ご注文ください。



■姿図は埋込形です。

■200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6
200V用(2P2E)実装数	0	1	2

■200V切替可能回路数(右端より)

総実装回路数	4	6	8
200V切替可能回路数	2	4	4