


































単3

主幹：単3中性線欠相保護付漏電遮断器

主幹	分岐回路数 +予備回路数	仕様 区分	型式	メーカー希望 小売価格 (円)	一 梱 入 数	姿図 外形寸法(タテ×ヨコ×フカサ)mm	回路図 寸法図番号(P.211~213)
3P、OC付 50A (30mA、高速形) GBU-53・1E	4+2	●	VG3504-2SH	19,800	5	 245×385×55 盤定格60A 	
	6+0	○	VG3506SH	21,600	5		
	4+2	●	VG3504-2H	19,800	5	 295×290×55 盤定格60A 	
	6+0	○	VG3506H	21,600	5		
	6+2	○	VG3506-2SiH	23,100	4	 240×460×64 盤定格60A 	
	8+0	○	VG3508SiH	24,900	4		
	6+2	○	VG3506-2H	23,100	5	 295×315×55 盤定格60A 	
	8+0	○	VG3508H	24,900	5		
	8+2	○	VG3508-2iH	25,000	4	 300×360×70 盤定格60A 	
	10+0	○	VG3510iH	26,800	4		
	8+4	○	VG3508-4iH	27,000	2	 300×400×70 盤定格60A 	
	10+2	○	VG3510-2iH	28,800	2		
	12+0	○	VG3512iH	30,600	2	 295×530×55 盤定格60A 	
	12+4	○	VG3512-4H	33,000	2		
	14+2	○	VG3514-2H	34,800	2	 315×570×60 盤定格60A 	
	16+0	○	VG3516H	36,600	2		
	14+4	○	VG3514-4H	35,900	2	 360×650×76 盤定格60A 	
	16+2	○	VG3516-2H	37,600	2		
	18+0	○	VG3518H	39,400	2	 360×650×76 盤定格60A 	
	18+4	○	VG3518-4iH	40,300	1		
	20+2	○	VG3520-2iH	42,100	1	 360×650×76 盤定格60A 	
	22+0	○	VG3522iH	43,900	1		

■200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	4	6~10	12~18	20~22
200V用(2P2E)実装数	1	2	4	6

■200V切替可能回路数(右端より)

総実装回路数	6, 8	12	16	18	総実装回路数
200V切替可能回路数	4	6	6	10	全回路

 住宅用分電盤規格適合品認定マーク