



















V
タイププラスチック製
露出・半埋込兼用形
色：マンセル10Y8.5/1**単3** 主幹：単3中性線欠相保護付漏電遮断器

主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	メーカー希望 小売価格 (円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm	回路図 寸法図番号(P.211~213)
3P OC付 50A (30mA、高速形) GBU-53・1E	4+2	☐	VLG3504-2iH	VLG35042iH3	21,900		
	6+0	☐	VLG3506iH	VLG3506iH3	23,500		
	6+2	☐	VLG3506-2iH	VLG35062iH3	25,300		
	8+0	☐	VLG3508iH	VLG3508iH3	27,000		
	8+2	☐	VLG3508-2iH	VLG35082iH3	27,200		
	10+0	☐	VLG3510iH	VLG3510iH3	29,000		
	8+4	☐	VLG3508-4iH	VLG35084iH3	31,500		
	10+2	☐	VLG3510-2iH	VLG35102iH3	33,000		
	12+0	☐	VLG3512iH	VLG3512iH3	35,000		
	10+4	☐	VLG3510-4iH	VLG35104iH3	36,000		
	12+2	☐	VLG3512-2iH	VLG35122iH3	37,800		
	14+0	☐	VLG3514iH	VLG3514iH3	39,600		
	14+4	☐	VLG3514-4iH	VLG35144iH3	40,600		
	16+2	☐	VLG3516-2iH	VLG35162iH3	42,400		
	18+0	☐	VLG3518iH	VLG3518iH3	44,200		
	18+4	☒	VLG3518-4iH	VLG35184iH3	54,400		
	20+2	☒	VLG3520-2iH	VLG35202iH3	56,100		
	22+0	☒	VLG3522iH	VLG3522iH3	57,900		
3P OC付 60A (30mA、高速形) GBU-63・1E	4+2	☐	VLG3604-2iH	VLG36042iH3	21,900		
	6+0	☐	VLG3606iH	VLG3606iH3	23,500		
	6+2	☐	VLG3606-2iH	VLG36062iH3	25,300		
	8+0	☐	VLG3608iH	VLG3608iH3	27,000		

次ページへ

■ 200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6~10	12~18	20以上
200V用(2P2E)実装数	0	1	2	4	6

住宅用分電盤規格適合品認定マーク