












全電力管内向け (リミッタースペースなし)

V タイプ

プラスチック製
露出・半埋込兼用形
(VG3304SiHは露出形)
色: マンセル10Y8.5/1

単3

主幹：単3中性線欠相保護付漏電遮断器

主幹	分岐回路数 + 予備回路数	仕様 区分	型式	ご注文品番	メーカー希望 小売価格 (円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm	回路図 ☐ 寸法図番号(P.217~218)
3P OC付 30A (30mA、高速形) GBU-3・1EA	3+1	☐	VG3303-1SiH	VG33031SiH3	13,000		
	4+0	☐	VG3304SiH	VG3304SiH3	13,900		
						150×300×60 盤定格30A  30	
	4+2	☐	VG3304-2SiH	VG33042SiH3	16,900		
	6+0	☐	VG3306SiH	VG3306SiH3	18,700		
						240×390×64 盤定格30A  31	
	4+2	☐	VG3304-2iH	VG33042iH3	16,900		
	6+0	☐	VG3306iH	VG3306iH3	18,700		
						300×290×70 盤定格30A  32	
	6+2	☐	VG3306-2SiH	VG33062SiH3	19,700		
	8+0	☐	VG3308SiH	VG3308SiH3	21,500		
						240×460×64 盤定格30A  33	
	6+2	☐	VG3306-2iH	VG33062iH3	19,700		
	8+0	☐	VG3308iH	VG3308iH3	21,500		
						300×325×70 盤定格30A  34	
	6+4	☐	VG3306-4iH	VG33064iH3	20,800		
	8+2	☐	VG3308-2iH	VG33082iH3	22,600		
	10+0	☐	VG3310iH	VG3310iH3	24,400	300×360×70 盤定格30A  35	
	8+4	☒	VG3308-4iH	VG33084iH3	24,700		
	10+2	☒	VG3310-2iH	VG33102iH3	26,500		
	12+0	☒	VG3312iH	VG3312iH3	28,200		
						300×400×70 盤定格30A  36	

■ 200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6~10	12~18	20以上
200V用(2P2E)実装数	0	1	2	4	6

 住宅用分電盤規格適合品認定マーク