










Aタイプ

扉付スチール製
色：マンセル2.5Y9/1

単3

主幹：単3中性線欠相保護付漏電遮断器







主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	露出 埋込	メーカー希望 小売価格 (円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm	回路図 □寸法図番号(P.222)
3P OC付 75A (30mA、高速形) GBU-73・1E	12+0	□	AG3712H	AG3712HS3 AG3712HF3	露出 埋込	41,500 42,300		
	14+2	□	AG3714-2H	AG37142HS3 AG37142HF3	露出 埋込	45,800 46,700		
	16+0	□	AG3716H	AG3716HS3 AG3716HF3	露出 埋込	47,500 48,400		
3P OC付 100A (30mA、高速形) GBU-103・1E	12+0	□	AG31012H	AG31012HS3 AG31012HF3	露出 埋込	53,700 54,600		
	14+2	□	AG31014-2H	AG310142HS3 AG310142HF3	露出 埋込	58,100 59,000		
	16+0	□	AG31016H	AG31016HS3 AG31016HF3	露出 埋込	59,800 60,700		



住宅用分電盤（全電力管内向け）

単3

主幹：単3中性線欠相保護付漏電遮断器

主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	露出 埋込	メーカー希望 小売価格 (円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm	回路図 □寸法図番号(P.223)
3P OC付 75A (30mA、高速形) GBU-73・1E	18+2	□	AG3718-2H	AG37182HS3 AG37182HF3	露出 埋込	59,300 60,200		
	20+0	□	AG3720H	AG3720HS3 AG3720HF3	露出 埋込	61,000 61,900		
	22+2	□	AG3722-2H	AG37222HS3 AG37222HF3	露出 埋込	63,800 64,700		
	24+0	□	AG3724H	AG3724HS3 AG3724HF3	露出 埋込	65,500 66,400		
3P OC付 100A (30mA、高速形) GBU-103・1E	18+2	□	AG31018-2H	AG310182HS3 AG310182HF3	露出 埋込	73,300 74,200		
	20+0	□	AG31020H	AG31020HS3 AG31020HF3	露出 埋込	75,000 75,900		
	22+2	□	AG31022-2H	AG310222HS3 AG310222HF3	露出 埋込	80,600 81,500		
	24+0	□	AG31024H	AG31024HS3 AG31024HF3	露出 埋込	82,300 83,200		

■200V用2P2E安全ブレーカ実装数(100V配線)

■200V切替可能回路数(右端より)

分岐回路数	3	4	6~10	12~18	20以上
200V用(2P2E)実装数	0	1	2	4	6

総実装回路数	18~20	22~24
200V切替可能回路数	10	12

住宅用分電盤規格適合品認定マーク