








安全ブレーカ

極数(P)・素子数(E)・フレーム(AF)		2P・1E・30AF						2P・2E・30AF						2P・1E・30AF					
定格電圧		110V						110/220V						110V					
		100V						100V						100V					
型式		B-1E						B-2E						B-1H					
定格電流 ・ ご注文品番		2A	B1E02																
		3A	B1E03																
		5A	B1E05																
				6A	B1E06						6A	B2E06							
				10A	B1E10						10A	B2E10							
								15A	B1E15				15A	B2E15					
								20A	B1E20				20A	B2E20		20A	B1H20		
			30A	B1E30						30A	B2E30						30A	B1H30	
メーカー希望小売価格(円)		1,760		910		880		1,300		1,250		1,100		1,150					
外観及び外形寸法(mm)		 A 70 B 32 C 40 D 57  <td colspan="6">  A 70 B 32 C 40 D 57  <td colspan="6">  A 70 B 32 C 40 D 57  </td></td>						 A 70 B 32 C 40 D 57  <td colspan="6">  A 70 B 32 C 40 D 57  </td>						 A 70 B 32 C 40 D 57 					
定格遮断容量(kA)		AC		110V	1.0		1.5		1.5		2.5								
				110/220V			1.5												
				220V															
		DC		460V															
				100V	0.1		0.3		0.3		0.3								
250V																			
標準接続方式		ソルダレス端子方式(当座金付)						ソルダレス端子方式(当座金付)						ソルダレス端子方式(当座金付)					
接続可能最大電線(mm ²)		8						8						8					
取付可能付属装置	接続方式		裏面形	SD		—		—		—		—							
			埋込形	FP		—		—		—									
	補助スイッチ		AX		—		—		—										
	警報スイッチ		AL		—		—		—										
	電圧引外し装置		SHT		—		—		—										
	不足電圧引外し装置		UVT		—		—		—										
	端子台		TB		—		—		—										
	トリップボタン		TRB		—		—		—										
	ハンドルロック		キャップ式LC		別売(LC-03)		別売(LC-03)		別売(LC-03)										
			施錠式 HL		—		—		—										
	外部操作ハンドル		HM, HA		—		—		—										
	機械的インターロック		MI		—		—		—										
	バリア		BA		—		—		—										
	端子カバー		表面形	TMC		付 属		付 属		付 属									
			裏面形	BTC		—		—		—									
引外し方式		熱動電磁		熱 動		熱 動		熱 動											
重量(kg)		0.09		0.10		0.11													
一梱入数		100		50		50													
特性, 寸法図記載ページ		P.279 ①, P.283 ①		P.279 ①, P.283 ①		P.279 ②, P.283 ①													

■定格電圧は最大使用可能電圧。■110/220Vは単3における220Vを表します。■付属装置は「付属装置」の項を参照。P.261～