



2P・2E・50AF			3P・3E・50AF			4P・3E・50AF			2P・2E・50AF			3P・3E・50AF			4P・3E・50AF			極数(P)・素子数(E)・フレーム(AF)																		
600V									250V									600V									AC DC		定格電圧							
● B-52FD			● B-53FD			● B-54FC			● B-52FKA			● B-53FKA			● B-54FKA			型式																		
5A	B52FD05		5A	B53FD05		5A	B54FC05		5A	B52FKA05		5A	B53FKA05		5A	B54FKA05	定格電流 ・ ご注文品番																			
10A	B52FD10		10A	B53FD10		10A	B54FC10		10A	B52FKA10		10A	B53FKA10		10A	B54FKA10																				
15A	B52FD15		15A	B53FD15		15A	B54FC15		15A	B52FKA15		15A	B53FKA15		15A	B54FKA15																				
20A	B52FD20		20A	B53FD20		20A	B54FC20		20A	B52FKA20		20A	B53FKA20		20A	B54FKA20																				
30A	B52FD30		30A	B53FD30		30A	B54FC30		30A	B52FKA30		30A	B53FKA30		30A	B54FKA30																				
40A	B52FD40		40A	B53FD40		40A	B54FC40		40A	B52FKA40		40A	B53FKA40		40A	B54FKA40																				
50A	B52FD50		50A	B53FD50		50A	B54FC50		50A	B52FKA50		50A	B53FKA50		50A	B54FKA50																				
13,100			17,300			27,200			28,000			35,000			66,800			メーカー希望小売価格(円)																		
NEW 									DC用はご指定ください																		外観及び外形寸法(mm)									
2P A 130 B 52 C 60 D 84			3P A 130 B 75 C 60 D 84			4P A 130 B 100 C 60 D 84			2P A 150 B 65 C 86 D 106			3P A 150 B 90 C 86 D 106			4P A 150 B 120 C 86 D 106																					
25									85									110V					定格													
10									50									220V					AC	遮断容量												
2.5									14									460V					(kA)													
									40									550V					DC													
									40									125V																		
																		250V																		
線押え方式(圧着端子使用可能)									線押え方式(圧着端子使用可能)									標準接続方式																		
22									22									接続可能最大電線(mm ²)																		
●									●									SD 裏面形									取付可能付属装置									
●									●									FP 埋込形																		
●									●									AX 補助スイッチ																		
●									●									AL 警報スイッチ																		
●									●									SHT 電圧引外し装置																		
●									●									UVT 不足電圧引外し装置																		
可能									可能									TB 端子台																		
付属									付属									TRB トリップボタン																		
別売(LC-2E)									別売(LC-1B)									別売(LC-2C)										LC キャップ式								
●									●									●										HL 施錠式								
HA-108			HA-108, HM-108			HA-107, HM-57			HA-106			HA-106, HM-106			HM, HA			外部操作ハンドル																		
●									●									MI 機械的インターロック																		
別売									電源側付属									BA									パリア									
別売(TMC-1)・4Pは2P用×2									別売(TMC-3C)・4Pは2P用×2									TMC 表面形									端子カバー									
別売(BTC-1)・4Pは2P用×2									別売(BTC-3C)・4Pは2P用×2									BTC 裏面形																		
完全電磁									完全電磁									引外し方式																		
0.53			0.74			0.95			1.4			1.8			2.3			重量(kg)																		
1									1									一梱入数																		
P. 280 ㉑, P. 296 ㉒									P. 280 ㉑, P. 297 ㉒									特性, 寸法図記載ページ																		

■ 定格電圧は最大使用可能電圧。■ 付属装置は「付属装置」の項を参照。P. 261～ ■ 適合圧着端子一覧表はP. 275

裏面形, 埋込形価格表

(フラッシュプレート:マンセル5Y7/1)

ご注文品番の後に裏面形はS、埋込形はFをつけてご注文ください。	SD 裏面形						FP 埋込形					
	B-52FD	B-53FD	B-54FC	B-52FKA	B-53FKA	B-54FKA	B-52FD	B-53FD	B-54FC	B-52FKA	B-53FKA	B-54FKA
メーカー希望小売価格(円)	14,400	19,200	29,700	29,300	36,900	69,300	16,210	21,240	33,120	31,110	38,940	72,720