

[illegible]

裏面形端子カバー

○10.5

M10ボルト付属

18

218

スタッド取付方向A方式
(標準仕様)

スタッド取付方向B方式
(受注仕様)

18

10

70

92

一体形絶縁ブッシング

取付板

106

81

68

51

35 35

ブッシング外径φ22.5

穴間寸法

遮断器外形

6-φ25穴

4-M4

200

218

247 (含ブッシング)

35 35

35 35

バースタッド方向標準 (A方式) で出荷します。

(2Pも同じです)

Technical drawings illustrating the M10 bolt attachment method for the panel.

Top View (Left): Shows the panel dimensions and stud positions. The overall width is 170, with a central section of 155 (middle) and 130, and side sections of 115 (left) and 115 (right). The overall height is 302, with a central section of 47.5. The stud positions are marked with circles and crosses. The distance between the studs is 35, 35, and 150.

Side View (Middle): Shows the panel, flash plate, and M10 bolt attachment. The bolt is labeled $\phi 10.5$ and M10 ボルト付属. The distance from the panel to the bolt is 18. The distance from the flash plate to the bolt is 118.5. The distance from the panel to the bolt is 216. The distance from the panel to the bolt is 14. The distance from the panel to the bolt is 28.

Front View (Right): Shows the panel dimensions and stud positions. The overall width is 170, with a central section of 155 (middle) and 130, and side sections of 115 (left) and 115 (right). The overall height is 302, with a central section of 47.5. The stud positions are marked with circles and crosses. The distance between the studs is 35, 35, and 150.

Bottom View (Right): Shows the panel dimensions and stud positions. The overall width is 170, with a central section of 155 (middle) and 130, and side sections of 115 (left) and 115 (right). The overall height is 302, with a central section of 47.5. The stud positions are marked with circles and crosses. The distance between the studs is 35, 35, and 150.

穴明寸法 (Hole Dimensions): Shows the dimensions for the hole in the panel. The overall width is 170, with a central section of 155 (middle) and 130, and side sections of 115 (left) and 115 (right). The overall height is 302, with a central section of 47.5. The hole is labeled 4-M5. The distance between the studs is 35, 35, and 150.

バースタッド方向標準 (A方式) で出荷します。