















単3

主幹：単3中性線欠相保護付漏電遮断器

主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	メーカー希望 小売価格 (円)	姿図 外形寸法(タテ×ヨコ×フサ)mm	回路図 寸法図番号(P.219~221)
3P OC付 40A (30mA、高速形) GBU-53・1E	4+2	☐	VG3404-2SiH	VG34042SiH3	19,800		
	6+0	☐	VG3406SiH	VG3406SiH3	21,600		
						240×390×64 盤定格60A 	
	4+2	☐	VG3404-2iH	VG34042iH3	19,800		
	6+0	☐	VG3406iH	VG3406iH3	21,600		
						300×290×70 盤定格60A 	
	6+2	☐	VG3406-2SiH	VG34062SiH3	23,100		
	8+0	☐	VG3408SiH	VG3408SiH3	24,900		
						240×460×64 盤定格60A 	
	6+2	☐	VG3406-2iH	VG34062iH3	23,100		
	8+0	☐	VG3408iH	VG3408iH3	24,900		
						300×325×70 盤定格60A 	
	8+2	☐	VG3408-2iH	VG34082iH3	25,000		
	10+0	☐	VG3410iH	VG3410iH3	26,800		
						300×360×70 盤定格60A 	
	8+4	☒	VG3408-4iH	VG34084iH3	27,000		
	10+2	☒	VG3410-2iH	VG34102iH3	28,800		
	12+0	☒	VG3412iH	VG3412iH3	30,600		
	12+4	☐	VG3412-4iH	VG34124iH3	33,000		
	14+2	☐	VG3414-2iH	VG34142iH3	34,800		
	16+0	☐	VG3416iH	VG3416iH3	36,600		
						320×540×70 盤定格60A 	
	14+4	☐	VG3414-4iH	VG34144iH3	34,900		
	16+2	☐	VG3416-2iH	VG34162iH3	37,600		
	18+0	☐	VG3418iH	VG3418iH3	39,400		
	18+4	☐	VG3418-4iH	VG34184iH3	40,300		
	20+2	☐	VG3420-2iH	VG34202iH3	42,100		
	22+0	☐	VG3422iH	VG3422iH3	43,900		
						360×650×76 盤定格60A 	

■200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6~10	12~18	20以上
200V用(2P2E)実装数	0	1	2	4	6