












Aタイプ

扉付スチール製
色:マンセル2.5Y9/1ご注文の際は埋込形か露出形か
ご指定ください。

単3

主幹：単3中性線欠相保護付漏電遮断器











主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	露出 埋込	メーカー希望 小売価格 (円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm	回路図 寸法図番号(P.224~225)
3P OC付 75A (30mA、高速形) GBU-73・1E	12+0	□	AG3712H	AG3712HS3	露出	41,500		
				AG3712HF3	埋込	42,300		
	14+2	□	AG3714-2H	AG37142HS3	露出	45,800		
				AG37142HF3	埋込	46,700		
	16+0	□	AG3716H	AG3716HS3	露出	47,500		
				AG3716HF3	埋込	48,400		
3P OC付 100A (30mA、高速形) GBU-103・1E	12+0	□	AG31012H	AG31012HS3	露出	53,700		
				AG31012HF3	埋込	54,600		
	14+2	□	AG31014-2H	AG310142HS3	露出	58,100		
				AG310142HF3	埋込	59,000		
	16+0	□	AG31016H	AG31016HS3	露出	59,800		
				AG31016HF3	埋込	60,700		



住宅用分電盤 (全電力管内向け)

単3

主幹：単3中性線欠相保護付漏電遮断器

主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	露出 埋込	メーカー希望 小売価格 (円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm	回路図 寸法図番号(P.225)
3P OC付 75A (30mA、高速形) GBU-73・1E	18+2	□	AG3718-2H	AG37182HS3	露出	59,300		
				AG37182HF3	埋込	60,200		
	20+0	□	AG3720H	AG3720HS3	露出	61,000		
				AG3720HF3	埋込	61,900		
	22+2	□	AG3722-2H	AG37222HS3	露出	63,800		
				AG37222HF3	埋込	64,700		
3P OC付 100A (30mA、高速形) GBU-103・1E	24+0	□	AG3724H	AG3724HS3	露出	65,500		
				AG3724HF3	埋込	66,400		
	18+2	□	AG31018-2H	AG310182HS3	露出	73,300		
				AG310182HF3	埋込	74,200		
	20+0	□	AG31020H	AG31020HS3	露出	75,000		
				AG31020HF3	埋込	75,900		
3P OC付 100A (30mA、高速形) GBU-103・1E	22+2	□	AG31022-2H	AG310222HS3	露出	80,600		
				AG310222HF3	埋込	81,500		
	24+0	□	AG31024H	AG31024HS3	露出	82,300		
				AG31024HF3	埋込	83,200		

主幹60Aについては別途お問合せください。

■200V用2P2E安全ブレーカ実装数(100V配線)

■200V切替可能回路数(右端より)

住宅用分電盤規格適合品認定マーク

分岐回路数	3	4	6~10	12~18	20以上
200V用(2P2E)実装数	0	1	2	4	6

総実装回路数	18~20	22~24
200V切替可能回路数	10	12