


安全ブレーカ

極数(P)・素子数(E)・フレーム(AF)		2P・1E・30AF						2P・2E・30AF						2P・1E・30AF																													
定格電圧		110V						110/220V						110V																													
		100V						100V						100V																													
型式		B-1E、B-1EA (15A、20A、30A)						B-2E,B-2EA (15A、20A、30A)						B-1H																													
定格電流 ・ ご注文品番		2A	B1E02																																								
		3A	B1E03																																								
		5A	B1E05																																								
				6A	B1E06							6A	B2E06																														
				10A	B1E10							10A	B2E10																														
							15A	B1EA15							15A	B2EA15																											
							20A	B1EA20							20A	B2EA20					20A	B1H20																					
				30A	B1EA30							30A	B2EA30									30A	B1H30																				
メーカー希望小売価格(円)		1,760						910						880						1,300						1,250						1,100						1,150					
外観及び外形寸法(mm)		 A 70 B 32 C 40 D 57 						 A 70 B 32 C 40 D 57						 A 70 B 32 C 40 D 57																													
定格遮断容量(kA)		AC		110V		1.0		1.5		1.5		1.5		2.5																													
				110/220V																																							
				220V																																							
				460V																																							
		DC		100V		0.1		0.3		0.3		0.3																															
				250V																																							
標準接続方式		ソルダレス端子方式(当座金付)						ソルダレス端子方式(当座金付)						ソルダレス端子方式(当座金付)																													
接続可能最大電線(mm²)		8						8						8																													
取付可能付属装置	接続方式		裏面形	SD		—		—		—		—																															
			埋込形	FP		—		—		—																																	
	補助スイッチ		AX		—		—		—																																		
	警報スイッチ		AL		—		—		—																																		
	電圧引外し装置		SHT		—		—		—																																		
	不足電圧引外し装置		UVT		—		—		—																																		
	端子台		TB		—		—		—																																		
	トリップボタン		TRB		—		—		—																																		
	キャップ式		LC		別売(LC-03)		別売(LC-03)		別売(LC-03)																																		
	施錠式		HL		—		—		—																																		
	外部操作ハンドル		HM, HA		—		—		—																																		
	機械的インターロック		MI		—		—		—																																		
バリア		BA		—		—		—																																			
端子カバー		表面形	TMC		付 属		付 属		付 属																																		
		裏面形	BTC		—		—		—																																		
引外し方式		熱動電磁		熱 動		熱 動		熱 動																																			
重量(kg)		0.09		0.10		0.11																																					
一梱入数		100		50		50																																					
特性, 寸法図記載ページ		P.281 ①, P.285 ①		P.281 ①, P.285 ①		P.281 ②, P.285 ①																																					

■定格電圧は最大使用可能電圧。■110/220Vは単3における220Vを表します。■付属装置は「付属装置」の項を参照。P.282～

配線用遮断器