



電子式配線用遮断器

配線用遮断器

極数(P)・素子数(E)・フレーム(AF)		3P・3E・1000AF	4P・3E・1000AF	3P・3E・1200AF	4P・3E・1200AF	3P・3E・1600AF	4P・3E・1600AF																																						
定格電圧	AC	600V		600V		600V																																							
	DC																																												
型式		●B-1003W	●B-1004W	●B-1203W	●B-1204W	●B-1603WA	●B-1604WA																																						
定格電流 ご注文品番		可調整 500A / 600A / 700A / 800A / 900A / 1000A B1003W	可調整 500A / 600A / 700A / 800A / 900A / 1000A B1004W	可調整 600A / 700A / 800A / 1000A / 1200A B1203W	可調整 600A / 700A / 800A / 1000A / 1200A B1204W	可調整 800A / 900A / 1000A / 1200A / 1400A / 1600A B1603WA	可調整 800A / 900A / 1000A / 1200A / 1400A / 1600A B1604WA																																						
メーカー希望小売価格(円)		695,000	1,177,000	864,000	1,224,000	1,083,000	1,530,000																																						
外観及び外形寸法(mm)		 <table><tr><th></th><th>3P</th><th>4P</th></tr><tr><td>A 410</td><td>A 410</td><td>A 410</td></tr><tr><td>A' 570</td><td>A' 570</td><td>A' 570</td></tr><tr><td>B 210</td><td>B 280</td><td>B 210</td></tr><tr><td>C 150</td><td>C 150</td><td>C 150</td></tr><tr><td>D 190</td><td>D 190</td><td>D 190</td></tr><tr><td>D' 298</td><td>D' 298</td><td>D' 298</td></tr></table>   <table><tr><th></th><th>3P</th><th>4P</th></tr><tr><td>A 410</td><td>A 410</td><td>A 410</td></tr><tr><td>A' 570</td><td>A' 570</td><td>A' 570</td></tr><tr><td>B 280</td><td>B 280</td><td>B 210</td></tr><tr><td>C 150</td><td>C 150</td><td>C 150</td></tr><tr><td>D 190</td><td>D 190</td><td>D 190</td></tr><tr><td>D' 298</td><td>D' 298</td><td>D' 298</td></tr></table> 			3P	4P	A 410	A 410	A 410	A' 570	A' 570	A' 570	B 210	B 280	B 210	C 150	C 150	C 150	D 190	D 190	D 190	D' 298	D' 298	D' 298		3P	4P	A 410	A 410	A 410	A' 570	A' 570	A' 570	B 280	B 280	B 210	C 150	C 150	C 150	D 190	D 190	D 190	D' 298	D' 298	D' 298
	3P	4P																																											
A 410	A 410	A 410																																											
A' 570	A' 570	A' 570																																											
B 210	B 280	B 210																																											
C 150	C 150	C 150																																											
D 190	D 190	D 190																																											
D' 298	D' 298	D' 298																																											
	3P	4P																																											
A 410	A 410	A 410																																											
A' 570	A' 570	A' 570																																											
B 280	B 280	B 210																																											
C 150	C 150	C 150																																											
D 190	D 190	D 190																																											
D' 298	D' 298	D' 298																																											
定格電圧	110V																																												
遮断容量 (kA)	220V	125		125		125																																							
	460V	85		85		85																																							
	550V	42		42		42																																							
	DC																																												
標準接続方式		バー端子方式		バー端子方式		バー端子方式																																							
接続可能最大電線(mm ²)																																													
取付可能付属装置	裏面形 SD	●		●		●(標準)																																							
	埋込形 FP	●		●		●																																							
	補助スイッチ AX	●		●		●																																							
	警報スイッチ AL	●		●		●																																							
	電圧引外し装置 SHT	●		●		●																																							
	不足電圧引外し装置 UVT	●		●		●																																							
	端子台 TB	可	能	可	能	可	能																																						
	トリップボタン TRB	付	属	付	属	付	属																																						
	キャップ式 LC	—		—		—																																							
	施錠式 HL	●		●		●																																							
外部操作ハンドルHM、HA	HA-801		HA-801		HA-801																																								
機械的インターロック MI	●		●		●																																								
バリア BA	電源側付属		電源側付属		電源側付属																																								
端子カバー	表面形 TMC	別売(TMC-6)		別売(TMC-6)		—																																							
	裏面形 BTC	—		—		—																																							
引外し方式		電子式可調整		電子式可調整		電子式可調整																																							
重量(kg)		26	33	26	33	37	49																																						
一梱入数		1		1		1																																							
特性、寸法図記載ページ		P.57 ^㉗ 、P.85 ^㉘		P.57 ^㉘ 、P.86 ^㉙		P.57 ^㉙ 、P.87 ^㉚																																							

■定格電圧は最大使用可能電圧。■付属装置は「付属装置」の項を参照。P.35～

裏面形、埋込形価格表

(フラッシュプレート：マンセル5Y7/1)

ご注文品番の後に 裏面形はS、 埋込形はFをつけて ご注文ください。	SD裏面形				FP埋込形					
	B-1003W	B-1004W	B-1203W	B-1204W	B-1003W	B-1004W	B-1203W	B-1204W	B-1603WA	B-1604WA
メーカー希望小売価格(円)	734,000	1,228,000	907,000	1,274,000	760,000	1,272,800	935,000	1,323,000	1,113,000	1,575,000