








全電力管内向け／リミッタースペースなし

単3 主幹:単3中性線欠相保護付漏電遮断器 付属機器取付スペース付 タデ 180mm×ヨコ 90mm

主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	メーカー希望 小売価格(円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm 回路図 □寸法図番号(P.244~245)
3P OC付 60A 30mA高速形	6+2	☐	VG3606-2P	VG36062P3	27,800	 314×500×77 盤定格60A  22
	8+0	☐	VG3608P	VG3608P3	29,600	
	10+2	☐	VG3610-2P	VG36102P3	34,400	 314×568×77 盤定格60A  23
	12+0	☐	VG3612P	VG3612P3	36,200	
						 314×661×77 盤定格60A  24
	14+2	☐	VG3614-2P	VG36142P3	40,600	
	16+0	☐	VG3616P	VG3616P3	42,400	
						 334×797×77 盤定格60A  25
	18+6	☐	VG3618-6P	VG36186P3	50,400	
3P OC付 75A 30mA高速形	6+2	☐	VG3706-2P	VG37062P3	32,500	 314×500×77 盤定格75A  22
	8+0	☐	VG3708P	VG3708P3	34,300	
	10+2	☐	VG3710-2P	VG37102P3	39,100	 314×568×77 盤定格75A  23
	12+0	☐	VG3712P	VG3712P3	40,900	
						 314×661×77 盤定格100A  24
	14+2	☐	VG3714-2P	VG37142P3	45,800	
	16+0	☐	VG3716P	VG3716P3	47,600	
						 334×797×77 盤定格100A  25
	18+6	☐	VG3718-6P	VG37186P3	53,900	

■200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6~10	12~18	20以上
200V用(2P2E)実装数	0	1	2	4	6