













全電力管内向け／リミッタースペースなし

単3 主幹:単3中性線欠相保護付配線用遮断器

主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	メーカー希望 小売価格(円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm 回路図 □寸法図番号(P.242~243)
3P 30A	4+2	■	VB3304-2	VB33042	15,800	  314×330×77 盤定格30A ¹³
	6+0	■	VB3306	VB3306	17,600	
	6+2	■	VB3306-2	VB33062	18,900	  314×364×77 盤定格30A ¹⁴
	8+0	■	VB3308	VB3308	20,700	
	8+2	■	VB3308-2	VB33082	21,700	  314×398×77 盤定格30A ¹⁵
	10+0	■	VB3310	VB3310	23,500	
	10+2	■	VB3310-2	VB33102	25,500	  314×432×77 盤定格30A ¹⁶
	12+0	■	VB3312	VB3312	27,300	
3P 50A (60A)	4+2	■	VB3504-2	VB35042	15,800	  314×330×77 盤定格60A ¹³
	6+0	■	VB3506	VB3506	17,600	
	6+2	■	VB3506-2	VB35062	18,900	  314×364×77 盤定格60A ¹⁴
	8+0	■	VB3508	VB3508	20,700	
	8+2	■	VB3508-2	VB35082	21,700	  314×398×77 盤定格60A ¹⁵
	10+0	■	VB3510	VB3510	23,500	
	10+2	■	VB3510-2	VB35102	25,500	  314×432×77 盤定格60A ¹⁶
	12+0	■	VB3512	VB3512	27,300	
	12+2	■	VB3512-2	VB35122	29,400	  314×466×77 盤定格60A ¹⁷
	14+0	■	VB3514	VB3514	31,200	

次ページへ

■200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6~10	12~18	20以上
200V用(2P2E)実装数	0	1	2	4	6

■ 主幹:40Aも組込可能です。別途お問合せください。