




電子式配線用遮断器

種数(P)・素子数(E)・フレーム(AF)		3P・3E・1000AF	4P・3E・1000AF	3P・3E・1200AF	4P・3E・1200AF	3P・3E・1600AF	4P・3E・1600AF																																																															
定格電圧		600V		600V		600V																																																																
AC																																																																						
DC																																																																						
型式		●B-1003W	●B-1004W	●B-1203W	●B-1204W	●B-1603WA	●B-1604WA																																																															
定格電流 ご注文品番		可調整 500A / 600A / 700A / 800A / 900A / 1000A B1003W	可調整 500A / 600A / 700A / 800A / 900A / 1000A B1004W	可調整 600A / 700A / 800A / 1000A / 1200A B1203W	可調整 600A / 700A / 800A / 1000A / 1200A B1204W	可調整 800A / 900A / 1000A / 1200A / 1400A / 1600A B1603WA	可調整 800A / 900A / 1000A / 1200A / 1400A / 1600A B1604WA																																																															
メーカー希望小売価格(円)		695,000	1,177,000	864,000	1,224,000	1,083,000	1,530,000																																																															
外観及び外形寸法(mm)		 <table><tr><th></th><th>3P</th><th>4P</th></tr><tr><td>A'410</td><td>A'410</td><td>A'410</td></tr><tr><td>A'570</td><td>A'570</td><td>A'570</td></tr><tr><td>B'210</td><td>B'210</td><td>B'210</td></tr><tr><td>C'150</td><td>C'150</td><td>C'150</td></tr><tr><td>D'190</td><td>D'190</td><td>D'190</td></tr><tr><td>D'298</td><td>D'298</td><td>D'298</td></tr></table> 			3P	4P	A'410	A'410	A'410	A'570	A'570	A'570	B'210	B'210	B'210	C'150	C'150	C'150	D'190	D'190	D'190	D'298	D'298	D'298	 <table><tr><th></th><th>3P</th><th>4P</th></tr><tr><td>A'410</td><td>A'410</td><td>A'410</td></tr><tr><td>A'570</td><td>A'570</td><td>A'570</td></tr><tr><td>B'210</td><td>B'210</td><td>B'210</td></tr><tr><td>C'150</td><td>C'150</td><td>C'150</td></tr><tr><td>D'190</td><td>D'190</td><td>D'190</td></tr><tr><td>D'298</td><td>D'298</td><td>D'298</td></tr></table> 			3P	4P	A'410	A'410	A'410	A'570	A'570	A'570	B'210	B'210	B'210	C'150	C'150	C'150	D'190	D'190	D'190	D'298	D'298	D'298	 <table><tr><th></th><th>3P</th><th>4P</th></tr><tr><td>A'410</td><td>A'410</td><td>A'640</td></tr><tr><td>A'640</td><td>A'640</td><td>A'640</td></tr><tr><td>B'210</td><td>B'210</td><td>B'280</td></tr><tr><td>C'150</td><td>C'150</td><td>C'150</td></tr><tr><td>D'190</td><td>D'190</td><td>D'190</td></tr><tr><td>D'298</td><td>D'298</td><td>D'298</td></tr></table> 			3P	4P	A'410	A'410	A'640	A'640	A'640	A'640	B'210	B'210	B'280	C'150	C'150	C'150	D'190	D'190	D'190	D'298	D'298	D'298
	3P	4P																																																																				
A'410	A'410	A'410																																																																				
A'570	A'570	A'570																																																																				
B'210	B'210	B'210																																																																				
C'150	C'150	C'150																																																																				
D'190	D'190	D'190																																																																				
D'298	D'298	D'298																																																																				
	3P	4P																																																																				
A'410	A'410	A'410																																																																				
A'570	A'570	A'570																																																																				
B'210	B'210	B'210																																																																				
C'150	C'150	C'150																																																																				
D'190	D'190	D'190																																																																				
D'298	D'298	D'298																																																																				
	3P	4P																																																																				
A'410	A'410	A'640																																																																				
A'640	A'640	A'640																																																																				
B'210	B'210	B'280																																																																				
C'150	C'150	C'150																																																																				
D'190	D'190	D'190																																																																				
D'298	D'298	D'298																																																																				
定格遮断容量(kA)		110V 220V 460V 550V 125V 250V		125 85 42		125 85 42																																																																
AC																																																																						
DC																																																																						
標準接続方式		バー端子方式		バー端子方式		バー端子方式																																																																
接続可能最大電線(mm²)																																																																						
取付可能付属装置	裏面形 SD	●		●		●(標準)																																																																
	埋込形 FP	●		●		●																																																																
	補助スイッチ AX	●		●		●																																																																
	警報スイッチ AL	●		●		●																																																																
	電圧引外し装置 SHT	●		●		●																																																																
	不足電圧引外し装置 UVT	●		●		●																																																																
	端子台 TB	可 能		可 能		可 能																																																																
	トリップボタン TRB	付 属		付 属		付 属																																																																
	キャップ式 LC	-		-		-																																																																
	ハンドルロック 施錠式 HL	●		●		●																																																																
	外部操作ハンドルHM、HA	HA-801		HA-801		HA-801																																																																
	機械的インターロック MI	●		●		●																																																																
バリア BA	電源側付属		電源側付属		電源側付属																																																																	
端子カバー	表面形 TMC	別売(TMC-6)		別売(TMC-6)		-																																																																
	裏面形 BTC	-		-		-																																																																
引外し方式		電子式可調整		電子式可調整		電子式可調整																																																																
重量(kg)		26	33	26	33	37	49																																																															
一梱入数		1		1		1																																																																
特性、寸法図記載ページ		P.61 ^㉔ 、P.91 ^㉔		P.61 ^㉔ 、P.92 ^㉔		P.61 ^㉔ 、P.93 ^㉔																																																																

■定格電圧は最大使用可能電圧。■付属装置は「付属装置」の項を参照。P.40～

裏面形、埋込形価格表

(フラッシュプレート：マンセル5Y7/1)

ご注文品番の後に 裏面形はS、 埋込形はFをつけて ご注文ください。	SD 裏面形				FP 埋込形					
	B-1003W	B-1004W	B-1203W	B-1204W	B-1003W	B-1004W	B-1203W	B-1204W	B-1603WA	B-1604WA
メーカー希望小売価格(円)	734,000	1,228,000	907,000	1,274,000	760,000	1,272,800	935,000	1,323,000	1,113,000	1,575,000