

極数(P)・素子数(E)・フレーム(AF)		2P・1E・30AF						2P・2E・30AF														
型式		GB-1ZA						GB-2ZA														
定格電圧		100V						100-100/200-200V														
動作時間		0.1秒以内						0.1秒以内														
定格感度電流		15mA			30mA			15mA			30mA											
定格電流 ご注文品番		5A	1ZA0515				5A	1ZA0530				5A	2ZA0515				5A	2ZA0530				
				6A	1ZA0615				6A	1ZA0630				6A	2ZA0615				6A	2ZA0630		
				10A	1ZA1015				10A	1ZA1030				10A	2ZA1015				10A	2ZA1030		
						15A	1ZA1515				15A	1ZA1530				15A	2ZA1515				15A	2ZA1530
						20A	1ZA2015				20A	1ZA2030				20A	2ZA2015				20A	2ZA2030
						30A	1ZA3015				30A	1ZA3030				30A	2ZA3015				30A	2ZA3030
メーカー希望小売価格(円)		5,400	4,300	4,000	5,400	4,300	4,000	6,000	4,800	4,600	6,000	4,800	4,600									
外観及び外形寸法(mm)		安全ブレーカ互換寸法						安全ブレーカ互換寸法														
B A D C		A 70 B 32 C 40 D 57 						A 70 B 32 C 40 D 57 														
定格	100V	1.5						1.5														
遮断容量	100/200V							1.5														
(kA)	200V							1.0														
	415V																					
標準接続方式		ソルダレス端子方式(当座金付)						ソルダレス端子方式(当座金付)														
接続可能最大電線(mm ²)		8						8														
中感度形		—						—														
時延形		—						—														
取付可能付属装置	裏面形	SD	—						—													
	埋込形	FP	—						—													
	補助スイッチ	AX	—						—													
	警報スイッチ	AL	—						—													
	テストリード線引出し	TBL	—						—													
	端子台	TB	—						—													
	キャップ式	LC	別売(LC-03)						別売(LC-03)													
	ハンドルロック	HL	—						—													
	施錠式	HA	—						—													
	外部操作ハンドル	BA	—						—													
バリア		—						—														
端子カバー	表面形	TMC	付 属						付 属													
	裏面形	BTC	—						—													
引外し方式		熱 動						熱 動														
重量(kg)		0.13						0.13														
一梱入数		50						50														
特性、寸法図記載ページ		P.161 ¹ 、P.165 ¹						P.161 ¹ 、P.165 ¹														

■100/200Vは単3における200Vを表します。■付属装置は「付属装置」の項を参照。P.141～