














全電力管内向け／リミッタースペースなし

単3 主幹：単3中性線欠相保護付漏電遮断器

主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	露出 埋込	メーカー希望 小売価格(円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm、□寸法図番号(P.299～301)	回路図
3P OC付 50A 30mA高速形	14+2	○	AG3514-2A	AG35142AS3	露出	33,300		
				AG35142AF3	埋込	40,000		
	16+0	○	AG3516A	AG3516AS3	露出	34,700		
				AG3516AF3	埋込	41,400		
	16+2	○	AG3516-2A	AG35162AS3	露出	36,000		
				AG35162AF3	埋込	42,700		
	18+0	○	AG3518A	AG3518AS3	露出	37,400		
				AG3518AF3	埋込	44,100		
	18+2	○	AG3518-2A	AG35182AS3	露出	38,000		
				AG35182AF3	埋込	44,700		
	20+0	○	AG3520A	AG3520AS3	露出	39,400		
				AG3520AF3	埋込	46,100		
	20+2	○	AG3520-2A	AG35202AS3	露出	40,000		
				AG35202AF3	埋込	46,900		
	22+0	○	AG3522A	AG3522AS3	露出	41,400		
				AG3522AF3	埋込	48,300		
	22+2	○	AG3522-2A	AG35222AS3	露出	43,800		
				AG35222AF3	埋込	50,800		
	24+0	○	AG3524A	AG3524AS3	露出	45,200		
				AG3524AF3	埋込	52,200		
	26+2	○	AG3526-2A	AG35262AS3	露出	51,300		
				AG35262AF3	埋込	59,300		
	28+0	○	AG3528A	AG3528AS3	露出	52,700		
				AG3528AF3	埋込	60,700		

住宅用分電盤(全電力管内向け)・フラットぱん

■200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6~10	12~18	20以上
200V用(2P2E)実装数	0	1	2	4	6

住宅用分電盤規格適合品認定マーク