



































全電力管内向け／リミッタースペースなし

単3 主幹:単3中性線欠相保護付漏電遮断器

主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	露出 埋込	メーカー希望 小売価格(円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm 寸法図番号(P.299~301)	回路図
3P OC付 60A 30mA高速形	6+2	○	AG3606-2A	AG36062AS3	露出	21,700		
				AG36062AF3	埋込	28,000		
	8+0	○	AG3608A	AG3608AS3	露出	23,100		
				AG3608AF3	埋込	29,400		
	8+4	○	AG3608-4A	AG36084AS3	露出	26,100		
				AG36084AF3	埋込	32,600		
	10+2	○	AG3610-2A	AG36102AS3	露出	27,500		
				AG36102AF3	埋込	34,000		
	12+0	○	AG3612A	AG3612AS3	露出	28,900		
				AG3612AF3	埋込	35,400		
	14+2	○	AG3614-2A	AG36142AS3	露出	33,300		
				AG36142AF3	埋込	40,000		
	16+0	○	AG3616A	AG3616AS3	露出	34,700		
				AG3616AF3	埋込	41,400		
	16+2	○	AG3616-2A	AG36162AS3	露出	36,000		
				AG36162AF3	埋込	42,700		
	18+0	○	AG3618A	AG3618AS3	露出	37,400		
				AG3618AF3	埋込	44,100		
	18+2	○	AG3618-2A	AG36182AS3	露出	38,000		
				AG36182AF3	埋込	44,700		
	20+0	○	AG3620A	AG3620AS3	露出	39,400		
				AG3620AF3	埋込	46,100		
	20+2	○	AG3620-2A	AG36202AS3	露出	40,000		
				AG36202AF3	埋込	47,000		
	22+0	○	AG3622A	AG3622AS3	露出	41,400		
				AG3622AF3	埋込	48,400		
	22+2	○	AG3622-2A	AG36222AS3	露出	43,800		
				AG36222AF3	埋込	50,800		
	24+0	○	AG3624A	AG3624AS3	露出	45,200		
				AG3624AF3	埋込	52,200		
	26+2	○	AG3626-2A	AG36262AS3	露出	51,300		
				AG36262AF3	埋込	59,300		
	28+0	○	AG3628A	AG3628AS3	露出	52,700		
				AG3628AF3	埋込	60,700		
							334x729x95 盤定格60A 21	

■200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6~10	12~18	20以上
200V用(2P2E)実装数	0	1	2	4	6

住宅用分電盤規格適合品認定マーク