

































全電力管内向け/リミッタースペースなし

単3 主幹:単3中性線欠相保護付漏電遮断器

主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	露出 埋込	メーカー希望 小売価格(円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm 寸法図番号(P.299~301)	回路図
3P OC付 100A 30mA高速形	14+2	○	AG31014-2A	AG310142AS3	露出	51,800		
				AG310142AF3	埋込	58,500		
	16+0	○	AG31016A	AG31016AS3	露出	53,200		
				AG31016AF3	埋込	59,900		
	16+2	○	AG31016-2A	AG310162AS3	露出	53,600		
				AG310162AF3	埋込	60,300		
	18+0	○	AG31018A	AG31018AS3	露出	55,000		
				AG31018AF3	埋込	61,700		
	18+2	○	AG31018-2A	AG310182AS3	露出	55,300		
				AG310182AF3	埋込	62,000		
	20+0	○	AG31020A	AG31020AS3	露出	56,700		
				AG31020AF3	埋込	63,400		
	20+2	○	AG31020-2A	AG310202AS3	露出	57,000		
				AG310202AF3	埋込	63,900		
	22+0	○	AG31022A	AG31022AS3	露出	58,400		
				AG31022AF3	埋込	65,300		
	22+2	○	AG31022-2A	AG310222AS3	露出	60,800		
				AG310222AF3	埋込	67,800		
	24+0	○	AG31024A	AG31024AS3	露出	62,200		
				AG31024AF3	埋込	69,200		
	26+2	○	AG31026-2A	AG310262AS3	露出	68,800		
				AG310262AF3	埋込	76,800		
	28+0	○	AG31028A	AG31028AS3	露出	70,200		
				AG31028AF3	埋込	78,200		
	26+6	○	AG31026-6A	AG310266AS3	露出	74,500		
				AG310266AF3	埋込	83,500		
	28+4	○	AG31028-4A	AG310284AS3	露出	75,900		
				AG310284AF3	埋込	84,900		
	30+2	○	AG31030-2A	AG310302AS3	露出	77,300		
				AG310302AF3	埋込	86,300		
	32+0	○	AG31032A	AG31032AS3	露出	78,700		
				AG31032AF3	埋込	87,700		

■200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6~10	12~18	20以上
200V用(2P2E)実装数	0	1	2	4	6

住宅用分電盤規格適合品認定マーク