

リミッタースペース付／北海道・東北・東京・中部・北陸・九州各電力管内向け

単3 主幹:単3中性線欠相保護付漏電遮断器

主幹	分岐回路数 +予備回路数	仕様 区分	型式	露出		メーカー希望 小売価格(円)	外形寸法 (タ×ヨ×ワ)mm
				露出	埋込		
3P OC付 40A 30mA高速形	8+0	●	ALG3408ACL	露出		34,600	314×432×110
				埋込		41,100	盤定格60A 
	12+0	●	ALG3412ACL	露出		45,700	314×500×110
				埋込		52,400	盤定格60A 
	16+0	●	ALG3416ACL	露出		56,800	314×568×110
				埋込		63,700	盤定格60A 
	20+0	●	ALG3420ACL	露出		65,400	314×661×110
				埋込		72,400	盤定格60A 
3P OC付 50A 30mA高速形	8+0	●	ALG3508ACL	露出		34,600	314×432×110
				埋込		41,100	盤定格60A 
	12+0	●	ALG3512ACL	露出		45,700	314×500×110
				埋込		52,400	盤定格60A 
	16+0	●	ALG3516ACL	露出		56,800	314×568×110
				埋込		63,700	盤定格60A 
	20+0	●	ALG3520ACL	露出		65,400	314×661×110
				埋込		72,400	盤定格60A 
3P OC付 60A 30mA高速形	8+0	●	ALG3608ACL	露出		34,600	314×432×110
				埋込		41,100	盤定格60A 
	12+0	●	ALG3612ACL	露出		45,700	314×500×110
				埋込		52,400	盤定格60A 
	16+0	●	ALG3616ACL	露出		56,800	314×568×110
				埋込		63,700	盤定格60A 
	20+0	●	ALG3620ACL	露出		65,400	314×661×110
				埋込		72,400	盤定格60A 
3P OC付 75A 30mA高速形	12+0	●	ALG3712ACL	露出		51,700	314×500×110
				埋込		58,400	盤定格75A 
	16+0	●	ALG3716ACL	露出		62,800	314×568×110
				埋込		69,700	盤定格75A 
	20+0	●	ALG3720ACL	露出		71,400	314×661×110
				埋込		78,400	盤定格75A 
	28+0	●	ALG3728ACL	露出		92,600	334×797×110
				埋込		101,600	盤定格75A 

住宅用分電盤(通電表示付住宅用分電盤)

■200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6~10	12~18	20以上
200V用(2P2E)実装数	0	1	2	4	6

住宅用分電盤規格適合品認定マーク