















全電力管内向け／リミッタースペースなし

単3 主幹：単3中性線欠相保護付漏電遮断器

主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	露出 埋込	メーカー希望 小売価格(円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm □寸法図番号(P.314～316)	回路図
3P OC付 30A 30mA高速形	3+1	○	KG3303-1H	KG33031HS33 KG33031HF33	露出 埋込	13,750		
	4+0	○	KG3304H	KG3304HS33 KG3304HF33	露出 埋込	14,650		
	4+2	○	KG3304-2H	KG33042HS3 KG33042HF3	露出 埋込	17,500		
	6+0	○	KG3306H	KG3306HS3 KG3306HF3	露出 埋込	19,300		
	6+2	○	KG3306-2H	KG33062HS33 KG33062HF33	露出 埋込	20,300		
								
3P OC付 40A 30mA高速形	6+0	○	KG3406H	KG3406HS3 KG3406HF3	露出 埋込	23,000		
	6+2	○	KG3406-2H	KG34062HS33 KG34062HF33	露出 埋込	24,000		
								
3P OC付 50A 30mA高速形	6+0	○	KG3506H	KG3506HS3 KG3506HF3	露出 埋込	23,000		
	6+2	○	KG3506-2H	KG35062HS33 KG35062HF33	露出 埋込	24,000		
								

住宅用分電盤(全電力管内向け)・Kタイプ

■200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6~10	12~18	20以上
200V用(2P2E)実装数	0	1	2	4	6

■200V切替可能回路数(右端より)

総実装回路数	4	6	8
200V切替可能回路数	2	4	4

住宅用分電盤規格適合品認定マーク