















全電力管内向け／リミッタースペースなし

単3 主幹：単3中性線欠相保護付配線用遮断器

主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	露出 埋込	メーカー希望 小売価格(円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm	回路図 □寸法図番号
3P 30A	6+2	●	AB3306-2A	AB33062AS	露出	18,400		
				AB33062AF	埋込	24,700		
	8+0	●	AB3308A	AB3308AS	露出	19,800		
				AB3308AF	埋込	26,100		
	10+2	●	AB3310-2A	AB33102AS	露出	24,200		
				AB33102AF	埋込	30,700		
3P 50A	12+0	●	AB3312A	AB3312AS	露出	25,600		
				AB3312AF	埋込	32,100		
	6+2	●	AB3506-2A	AB35062AS	露出	18,400		
				AB35062AF	埋込	24,700		
	8+0	●	AB3508A	AB3508AS	露出	19,800		
				AB3508AF	埋込	26,100		
	10+2	●	AB3510-2A	AB35102AS	露出	24,200		
				AB35102AF	埋込	30,700		
	12+0	●	AB3512A	AB3512AS	露出	25,600		
				AB3512AF	埋込	32,100		
	14+2	●	AB3514-2A	AB35142AS	露出	30,000		
				AB35142AF	埋込	36,700		
	16+0	●	AB3516A	AB3516AS	露出	31,400		
				AB3516AF	埋込	38,100		
	16+2	●	AB3516-2A	AB35162AS	露出	32,700		
				AB35162AF	埋込	39,400		
	18+0	●	AB3518A	AB3518AS	露出	34,100		
				AB3518AF	埋込	40,800		
	18+2	●	AB3518-2A	AB35182AS	露出	34,700		
				AB35182AF	埋込	41,400		
	20+0	●	AB3520A	AB3520AS	露出	36,100		
				AB3520AF	埋込	42,800		

■外形寸法図 P.353～ ■図番 14～18

■ 主幹：40Aも組み込み可能です。ご用命ください。

■200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6～10	12～18	20以上
200V用(2P2E)実装数	0	1	2	4	6