






















全電力管内向け/リミッタースペースなし

単3 主幹:単3中性線欠相保護付配線用遮断器

付属機器取付スペース付 タテ ヨコ フカサ 180×90×58

主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	露出 埋込	メーカー希望 小売価格(円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm	回路図 寸法図番号
3P 30A	6+2	●	AB3306-2PA	AB33062PAS	露出	21,100		
				AB33062PAF	埋込	27,800		
	8+0	●	AB3308PA	AB3308PAS	露出	22,500		
				AB3308PAF	埋込	29,200		
	8+2	●	AB3308-2PA	AB33082PAS	露出	24,400		
				AB33082PAF	埋込	31,100		
	10+0	●	AB3310PA	AB3310PAS	露出	25,800		
				AB3310PAF	埋込	32,500		
	10+2	●	AB3310-2PA	AB33102PAS	露出	27,700		
				AB33102PAF	埋込	34,600		
	12+0	●	AB3312PA	AB3312PAS	露出	29,100		
				AB3312PAF	埋込	36,000		
3P 50A	6+2	●	AB3506-2PA	AB35062PAS	露出	21,100		
				AB35062PAF	埋込	27,800		
	8+0	●	AB3508PA	AB3508PAS	露出	22,500		
				AB3508PAF	埋込	29,200		
	8+2	●	AB3508-2PA	AB35082PAS	露出	24,400		
				AB35082PAF	埋込	31,100		
	10+0	●	AB3510PA	AB3510PAS	露出	25,800		
				AB3510PAF	埋込	32,500		
	10+2	●	AB3510-2PA	AB35102PAS	露出	27,700		
				AB35102PAF	埋込	34,600		
	12+0	●	AB3512PA	AB3512PAS	露出	29,100		
				AB3512PAF	埋込	36,000		
	12+2	●	AB3512-2PA	AB35122PAS	露出	31,000		
				AB35122PAF	埋込	37,900		
	14+0	●	AB3514PA	AB3514PAS	露出	32,400		
				AB3514PAF	埋込	39,300		
	14+2	●	AB3514-2PA	AB35142PAS	露出	34,200		
				AB35142PAF	埋込	41,200		
	16+0	●	AB3516PA	AB3516PAS	露出	35,600		
				AB3516PAF	埋込	42,600		
	18+2	●	AB3518-2PA	AB35182PAS	露出	42,200		
				AB35182PAF	埋込	50,200		
	20+0	●	AB3520PA	AB3520PAS	露出	43,600		
				AB3520PAF	埋込	51,600		

■外形寸法図 P.353~ ■図番 23~28

■主幹:40Aも組込可能です。ご用命ください。

■200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6~10	12~18	20以上
200V用(2P2E)実装数	0	1	2	4	6