



















リミッタースペース付／北海道・東北・東京・中部・北陸・九州各電力管内向け

単3 主幹：単3中性線欠相保護付漏電遮断器

主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	メーカー希望 小売価格(円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm	回路図 □寸法図番号
3P OC付 30A 30mA高速形	2+2	○	VLG3302-2C	VLG33022C3	11,000	 314×330×77 盤定格30A 	
	4+0	○	VLG3304C	VLG3304C3	12,500		
	4+2	○	VLG3304-2C	VLG33042C3	12,500	 314×364×77 盤定格30A 	
	6+0	○	VLG3306C	VLG3306C3	13,900		
	6+2	○	VLG3306-2C	VLG33062C3	17,200	 314×398×77 盤定格30A 	
	8+0	○	VLG3308C	VLG3308C3	18,600		
	4+2	○	VLG3304-2	VLG330423	13,400	 314×432×77 盤定格30A 	
	6+0	○	VLG3306	VLG33063	14,800		
	6+2	○	VLG3306-2	VLG330623	18,000	 314×432×77 盤定格30A 	
	8+0	○	VLG3308	VLG33083	19,400		
	8+2	○	VLG3308-2	VLG330823	20,500	 314×466×77 盤定格30A 	
	10+0	○	VLG3310	VLG33103	21,900		
	8+4	○	VLG3308-4	VLG330843	23,600	 314×500×77 盤定格30A 	
	10+2	○	VLG3310-2	VLG331023	25,000		
	12+0	○	VLG3312	VLG33123	26,400		

■外形寸法図 P.360～ ■図番 30～36

■200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6～10	12～18	20以上
200V用(2P2E)実装数	0	1	2	4	6

住宅用分電盤規格適合品認定マーク