
















全電力管内向け／リミッタースペースなし

単3 主幹:単3中性線欠相保護付漏電遮断器 付属機器取付スペース付 タテヨコ 180mm×90mm

主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	メーカー希望 小売価格(円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm	回路図 □寸法図番号
3P OC付 30A 30mA高速形	6+2	○	VG3306-2P	VG33062P3	21,500		
	8+0	○	VG3308P	VG3308P3	22,900		
	8+2	○	VG3308-2P	VG33082P3	23,400		
	10+0	○	VG3310P	VG3310P3	24,800		
	10+2	○	VG3310-2P	VG33102P3	26,500		
	12+0	○	VG3312P	VG3312P3	27,900		
						314×500×77 盤定格30A 	60
3P OC付 40A 30mA高速形	6+2	○	VG3406-2P	VG34062P3	23,500		
	8+0	○	VG3408P	VG3408P3	24,900		
	8+2	○	VG3408-2P	VG34082P3	26,800		
	10+0	○	VG3410P	VG3410P3	28,200		
	10+2	○	VG3410-2P	VG34102P3	30,000		
	12+0	○	VG3412P	VG3412P3	31,400		
	12+2	○	VG3412-2P	VG34122P3	33,300		
	14+0	○	VG3414P	VG3414P3	34,700		
	14+2	○	VG3414-2P	VG34142P3	36,500		
	16+0	○	VG3416P	VG3416P3	37,900		
	18+2	○	VG3418-2P	VG34182P3	43,500		
	20+0	○	VG3420P	VG3420P3	44,900		
						314×500×77 盤定格60A 	60
						314×534×77 盤定格60A 	61
						314×568×77 盤定格60A 	62
						314×627×77 盤定格60A 	63
						314×661×77 盤定格60A 	64
						334×729×77 盤定格60A 	65

■外形寸法図 P.360～ ■図番 60～65

■200V用2P2E安全ブレーカ実装数(100V配線)

分岐回路数	3	4	6~10	12~18	20以上
200V用(2P2E)実装数	0	1	2	4	6

住宅用分電盤規格適合品認定マーク