












全電力管内向け／リミッタースペースなし

単3

主幹：単3中性線欠相保護付漏電遮断器

付属機器取付スペース付

タテヨコ
180mm×90mm

主幹	分岐回路数 +予備回路数	仕様 区分	型式	ご注文品番	メーカー希望 小売価格(円)	姿図 外形寸法(タテ×ヨコ×フカサ)mm	回路図 □寸法図番号	
3P OC付 75A 30mA高速形	14+2	○	VG3714-2P	VG37142P3	42,500		 スペース	
	16+0	○	VG3716P	VG3716P3	43,900			
	18+2	○	VG3718-2P	VG37182P3	49,500		 スペース	
	20+0	○	VG3720P	VG3720P3	50,900			
	18+6	○	VG3718-6P	VG37186P3	54,200		 スペース	
	20+4	○	VG3720-4P	VG37204P3	55,600			
22+2	○	VG3722-2P	VG37222P3	57,000				
	24+0	○	VG3724P	VG3724P3	58,400	334×797×77 盤定格100A  66	 スペース	
3P OC付 100A 30mA高速形	14+2	○	VG31014-2P	VG310142P3	53,500			 スペース
	16+0	○	VG31016P	VG31016P3	54,900			
	18+2	○	VG31018-2P	VG310182P3	60,500		 スペース	
	20+0	○	VG31020P	VG31020P3	61,900			
	18+6	○	VG31018-6P	VG310186P3	65,200		 スペース	
	20+4	○	VG31020-4P	VG310204P3	66,600			
22+2	○	VG31022-2P	VG310222P3	68,000				
	24+0	○	VG31024P	VG31024P3	69,400	334×797×77 盤定格100A  66		

■外形寸法図 P.360～ ■図番 64～66

■200V用2P2E安全ブレーカ実装数(100V配線)					
分岐回路数	3	4	6~10	12~18	20以上
200V用(2P2E)実装数	0	1	2	4	6