

65A以上

負荷の種類	時定数 L/R(ms)	電圧 DC(V)	直列 接点数	フレームと定格使用電流(A)								接点接続方法
				65HA	80HA	100HA 125HA	150HA	200HA 250HA	300HA 400HA			
抵抗負荷 DC1,DC12級	1以下	24	1	70	90	120	170	200	300			
		48	1	70	90	120	170	200	300			
			2	70	90	120	170	200	300			
		110	2	70	90	120	170	200	300			
			3	70	90	120	170	200	300			
		220	3	70	90	120	170	200	300			
直流モータ負荷 DC2,DC4級	15以下	24	1	25	35	40	60	100	150			
		48	2	25	50	60	80	120	150			
			3	35	80	90	120	180	200			
		110	2	15	30	40	60	100	150			
			3	30	60	80	100	150	200			
		220	3	12	30	40	60	80	100			
コイル負荷	40以下	24	1	10	20	20						
		48	1	10	20	20						
			2	25	50	60						
		110	2	10	20	20						
			3	25	50	60						
		220	3	5	7	7						
コイル負荷 DC13級	100以下	24	1	7	10	10						
		48	1	7	10	10						
			2	15	30	35						
		110	2	7	10	10						
			3	15	30	35						
		220	3	—	—	—						